

PRIMARY VOLTAGE — 2 X 117V 50/60 Hz (CONT.)

Part Number	Nominal Power (VA)	Secondary Voltage (Volts)	Secondary Current (Amps)	Core Loss (Watts)	Copper Loss (Watts)	OD x H Inches (mm)	Weight Lbs. (kg)	Mounting Hardware
AA50502006	50	2 x 6	4.2	8.6	0.45	3.2 x 1.4 (81 x 36)	1.6 (0.7)	#10
AA50502009		2 x 9	2.8	8.6	0.45			
AA50502012		2 x 12	2.1	8.6	0.45			
AA50502015		2 x 15	1.7	8.6	0.45			
AA50502018		2 x 18	1.4	8.6	0.45			
AA50502022		2 x 22	1.1	8.6	0.45			
AA50502024		2 x 24	1	8.6	0.45			
AA50952009	95	2 x 9	2.8	16.0	0.90	3.9 x 1.5 (99 x 38)	2.2 (1)	1/4"
AA50952012		2 x 12	2.1	16.0	0.90			
AA50952015		2 x 15	3.2	16.0	0.90			
AA50952018		2 x 18	2.6	16.0	0.90			
AA50952022		2 x 22	2.2	16.0	0.90			
AA50952024		2 x 24	2	16.0	0.90			
AA50952028		2 x 28	1.7	16.0	0.90			
AA50952030		2 x 30	1.6	16.0	0.90			
AA51402012	140	2 x 12	5.8	19.0	1.20	3.9 x 1.9 (99 x 48)	3 (1.4)	1/4"
AA51402015		2 x 15	4.7	19.0	1.20			
AA51402018		2 x 18	3.9	19.0	1.20			
AA51402022		2 x 22	3.2	19.0	1.20			
AA51402024		2 x 24	2.9	19.0	1.20			
AA51402028		2 x 28	2.5	19.0	1.20			
AA51402030		2 x 30	2.3	19.0	1.20			
AA51402117	2 x 117	0.6	19.0	1.20				
AA51852012	185	2 x 12	7.7	20.0	1.40	4.5 x 1.9 (114 x 48)	4 (1.8)	1/4"
AA51852015		2 x 15	6.16	20.0	1.40			
AA51852018		2 x 18	5.1	20.0	1.40			
AA51852022		2 x 22	4.2	20.0	1.40			
AA51852024		2 x 24	3.9	20.0	1.40			
AA51852028		2 x 28	3.3	20.0	1.40			
AA51852030		2 x 30	3.1	20.0	1.40			
AA51852117		2 x 117	0.8	20.0	1.40			
AA52402015	240	2 x 15	8	22.0	1.70	4.5 x 2.1 (114 x 53)	4.8 (2.2)	1/4"
AA52402018		2 x 18	6.7	22.0	1.70			
AA52402024		2 x 24	5	22.0	1.70			
AA52402030		2 x 30	4	22.0	1.70			
AA52402038		2 x 38	3.2	22.0	1.70			
AA52402117		2 x 117	1	22.0	1.70			