



PRIMARY VOLTAGE — 2 X 117V 50/60 Hz (CONT.)

Part Number	Nominal Power (VA)	Secondary Voltage (Volts)	Secondary Current (Amps)	Core Loss (Watts)	Copper Loss (Watts)	OD x H Inches (mm)	Weight Lbs. (kg)	Mounting Hardware
AA53002015		2 x 15	10	22.0	1.70			
AA53002018		2 x 18	8.3	22.0	1.70			
AA53002024	300	2 x 24	6.2	22.0	1.70	4.6 x 2.6 (117 x 66)	5.7 (2.6)	1/4"
AA53002030		2 x 30	5	22.0	1.70			
AA53002038		2 x 38	5	22.0	1.70			
AA53002117		2 x 117	1.3	22.0	1.70			
AA53752018		2 x 18	10.4	27.0	2.00			
AA53752024		2 x 24	7.8	27.0	2.00			
AA53752030	375	2 x 30	6.3	27.0	2.00	5.4 x 2.0 (137 x 51)	6.7 (3)	1/4"
AA53752038		2 x 38	4.9	27.0	2.00			
AA53752117		2 x 117	4.9	27.0	2.00			
AA54602024			2 x 24	9.6	31.0			
AA54602030	460	2 x 30	7.7	31.0	2.40	5.4 x 2.6 (137 x 66)	7.9 (3.6)	1/4"
AA54602038		2 x 38	6	31.0	2.40			
AA54602117		2 x 117	2	31.0	2.40			
AA56252024			2 x 24	13	36.0			
AA56252030		2 x 30	10.4	36.0	3.10			
AA56252033	625	2 x 33	9.5	36.0	3.10	5.5 x 3.2 (140 x 81)	9.5 (4.3)	1/4"
AA56252038		2 x 38	8.2	36.0	3.10			
AA56252117		2 x 117	2.7	36.0	3.10			
AA58002024			2 x 24	16.7	45.0			
AA58002030		2 x 30	13.3	45.0	3.80			
AA58002038	800	2 x 38	10.5	45.0	3.80	6.4 x 2.7 (163 x 69)	12.3 (5.6)	5/16"
AA58002048		2 x 48	8.2	45.0	3.80			
AA58002117		2 x 117	3.4	45.0	3.80			
AA59902024			2 x 24	20.6	45.0			
AA59902042	990	2 x 42	11.8	45.0	3.80	6.5 x 3.0 (165 x 76)	15.2 (6.9)	5/16"
AA59902055		2 x 55	9	45.0	3.80			
AA59902117		2 x 117	4.2	45.0	3.80			

Note: Electrical measurements @ 20°C ambient temperature. All data subject to change without prior notice.

Winding Configurations With Color Codes

Dual 117V 50/60Hz Primaries w/ Dual Secondaries
Multiple primaries must be connected in series or parallel.

