



PRIMARY VOLTAGE — 120V 60Hz

Part Number	Nominal Power (VA)	Secondary Voltage (Volts)	Secondary Current (Amps)	Core Loss (Watts)	Copper Loss (Watts)	OD x H Inches (mm)	Weight Lbs. (kg)	Mounting Hardware
AA50182009	18	2 x 9	1.0	3.0	0.20	2.5 x 1.3 (64 x 33)	0.7 (0.3)	#8
AA50182012		2 x 12	0.7	3.0	0.20			
AA50182015		2 x 15	0.6	3.0	0.20			
AA50182018		2 x 18	0.5	3.0	0.20			
AA50362009	36	2 x 9	2.0	5.8	0.25	2.9 x 1.5 (74 x 38)	1.1 (0.5)	#10
AA50362012		2 x 12	1.5	5.8	0.25			
AA50362015		2 x 15	1.2	5.8	0.25			
AA50362018		2 x 18	1.0	5.8	0.25			
AA50602009	60	2 x 9	3.3	8.6	0.45	3.3 x 1.4 (84 x 36)	1.6 (0.7)	#10
AA50602012		2 x 12	2.5	8.6	0.45			
AA50602015		2 x 15	2.0	8.6	0.45			
AA50602018		2 x 18	1.7	8.6	0.45			
AA50902012	90	2 x 12	3.8	12.0	0.60	3.7 x 1.5 (94 x 38)	1.9 (0.9)	#10
AA50902015		2 x 15	3.0	12.0	0.60			
AA50902018		2 x 18	2.5	12.0	0.60			
AA50902022		2 x 22	2.0	12.0	0.60			
AA51152012	115	2 x 12	4.8	16.0	0.90	3.9 x 1.5 (99 x 38)	2.2 (1)	1/4"
AA51152015		2 x 15	3.8	16.0	0.90			
AA51152018		2 x 18	3.2	16.0	0.90			
AA51152022		2 x 22	2.6	16.0	0.90			
AA51702012	170	2 x 12	7.1	19.0	1.20	3.9 x 1.9 (99 x 48)	3.1 (1.4)	1/4"
AA51702015		2 x 15	5.7	19.0	1.20			
AA51702018		2 x 18	4.7	19.0	1.20			
AA51702022		2 x 22	3.9	19.0	1.20			
AA52201220	220	220	1.0	20.0	1.40	4.5 x 1.8 (114 x 46)	4 (1.8)	1/4"
AA52202018		2 x 18	6.1	20.0	1.40			
AA52202022		2 x 22	5.0	20.0	1.40			
AA52202024		2 x 24	4.6	20.0	1.40			
AA53601220	360	220	1.6	22.0	1.70	4.5 x 2.4 (114 x 61)	5.4 (2.5)	1/4"
AA53602024		2 x 24	7.5	22.0	1.70			
AA53602030		2 x 30	6.0	22.0	1.70			
AA53602033		2 x 33	5.5	22.0	1.70			
AA53602038		2 x 38	4.7	22.0	1.70			
AA54501220	450	220	2.1	27.0	2.00	5.4 x 2 (137 x 51)	6.5 (3)	1/4"
AA54502030		2 x 30	7.5	27.0	2.00			
AA54502033		2 x 33	6.8	27.0	2.00			
AA54502038		2 x 38	5.9	27.0	2.00			