



480 VOLTS, 3% Z, 60 Hz (600 VOLTS, 2.4% Z; 240 VOLTS, 6% Z)

Catalog Number	Motor*				Dimensions			Design Figures	Weight (Lbs.)(Kg.)
	H.P.	Amp	Reactor Amp	uH	Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)		
ALRB002LWE	1	2.1	2	11027	9.68 (24.6)	4.75 (12.1)	4.5 (11.4)	A	10 (4.5)
ALRB003LWE	1.5	3	3	7351	9.68 (24.6)	4.75 (12.1)	4.5 (11.4)	A	10 (4.5)
ALRB004LWE	2	3.4	4	5513	9.68 (24.6)	4.75 (12.1)	4.5 (11.4)	A	10 (4.5)
ALRB006LWE	3	4.8	6	3676	9.68 (24.6)	4.75 (12.1)	4.5 (11.4)	A	10 (4.5)
ALRB008LWE	5	7.6	8	2757	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	24 (10.9)
ALRB012LWE	7.5	11	12	1838	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	24 (10.9)
ALRB016LWE	10	14	16	1378	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	25 (11.3)
ALRB025LWE	15	21	25	882	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	28 (12.7)
ALRB027LWE	20	27	27	817	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	28 (12.7)
ALRB035LWE	25	34	35	630	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	32 (14.5)
ALRB045LWE	30	40	45	490	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	33 (15.0)
ALRB055LWE	40	52	55	401	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	73 (33.1)
ALRB080LWE	60	77	80	276	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	75 (34.0)
ALRB110LWE	75	96	110	200	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	78 (35.4)
ALRB130LWE	100	124	130	170	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	85 (38.6)
ALRB160LWE	125	156	160	138	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	87 (39.5)

* Motor HP and Amp rated at 480 volts.

480 VOLTS, 5% Z, 60 Hz (600 VOLTS, 4% Z; 240 VOLTS, 10% Z)

Catalog Number	Motor*				Dimensions			Design Figures	Weight (Lbs.)(Kg.)
	H.P.	Amp	Reactor Amp	uH	Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)		
ALRC002LWE	1	2.1	2	18378	9.68 (24.6)	4.75 (12.1)	4.5 (11.4)	A	10 (4.5)
ALRC003LWE	1.5	3	3	12252	9.68 (24.6)	4.75 (12.1)	4.5 (11.4)	A	10 (4.5)
ALRC004LWE	2	3.4	4	9189	9.68 (24.6)	4.75 (12.1)	4.5 (11.4)	A	10 (4.5)
ALRC006LWE	3	4.8	6	6126	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	24 (10.9)
ALRC008LWE	5	7.6	8	4594	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	24 (10.9)
ALRC012LWE	7.5	11	12	3063	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	26 (11.8)
ALRC016LWE	10	14	16	2297	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	28 (12.7)
ALRC025LWE	15	21	25	1470	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	32 (14.5)
ALRC027LWE	20	27	27	1361	11.5 (29.2)	10.31 (26.2)	7.13 (18.1)	B	32 (14.5)
ALRC035LWE	25	34	35	1050	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	74 (33.6)
ALRC045LWE	30	40	45	817	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	75 (34.0)
ALRC055LWE	40	52	55	668	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	75 (34.0)
ALRC080LWE	60	77	80	459	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	85 (38.6)
ALRC110LWE	75	96	110	334	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	107 (48.5)
ALRC130LWE	100	124	130	263	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	107 (48.5)
ALRC160LWE	125	156	160	230	11.83 (30.0)	14.17 (36.0)	8.82 (22.4)	C	121 (54.9)

* Motor HP and Amp rated at 480 volts.

