



BOLT-IN BREAKERS
480 PRIMARY VOLTS — 240/120 SECONDARY VOLTS — 1Ø, 60 Hz

Single Phase

kVA	Catalog Number	Secondary Maximum Circuit ①		Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)
		120 V (1-pole)	240 V (2-pole)				
5.0	PT0B1150005LS	16	8	38.00 (96.5)	15.88 (40.3)	11.00 (27.9)	165 (74.8)
7.5	PT0B1150007LS	16	8	38.00 (96.5)	15.88 (40.3)	11.00 (27.9)	165 (74.8)
10.0	PT0B1150010LS	16	8	38.00 (96.5)	17.13 (43.5)	12.38 (31.4)	240 (108.8)
15.0	PT0B1150015LS	16	8	38.00 (96.5)	17.13 (43.5)	12.38 (31.4)	240 (109.0)
25.0	PT0B1150025LS	28	14	45.20 (114.8)	17.88 (45.4)	13.50 (34.3)	330 (150.0)

① The number of secondary circuits shown is only a representation of circuits. Please contact the factory for exact number of secondary circuits available.

304 STAINLESS STEEL/ BOLT-IN BREAKERS
480 PRIMARY VOLTS — 240/120 SECONDARY VOLTS — 1Ø, 60 Hz

Single Phase

kVA	Catalog Number	Secondary Maximum Circuit ①		Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)
		120 V (1-pole)	240 V (2-pole)				
5.0	PT0B1150005SS	16	8	38.00 (96.5)	15.88 (40.3)	11.00 (27.9)	165 (74.8)
7.5	PT0B1150007SS	16	8	38.00 (96.5)	15.88 (40.3)	11.00 (27.9)	165 (74.8)
10.0	PT0B1150010SS	16	8	34.38 (87.3)	17.13 (43.5)	12.38 (31.4)	240 (108.8)
15.0	PT0B1150015SS	16	8	34.38 (87.3)	17.13 (43.5)	12.38 (31.4)	240 (109.0)
25.0	PT0B1150025SS	28	14	41.88 (106.4)	17.88 (45.4)	13.50 (34.3)	330 (150.0)

① The number of secondary circuits shown is only a representation of circuits. Please contact the factory for exact number of secondary circuits available.

BOLT-IN BREAKERS
480 VOLTS to 240/120 VOLTS

Circuit Breaker Data

kVA	480 Volts primary breakers	240/120 Volts secondary main	Maximum Rating of Secondary Breakers
5.0	ED42B025L (25A)	B230H (30A)	20 amps
7.5	ED42B025L (25A)	B240H (40A)	30 amps
10.0	ED42B035L (35A)	B250H (50A)	40 amps
15.0	ED42B050L (50A)	B270H (70A)	60 amps
25.0	ED42B090L (90A)	B2125 (125A)	100 amps

