



SNAP-IN BREAKERS

480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz

Three Phase

kVA	Catalog Number	Secondary Maximum Circuit ①		Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)
		10 120 V (1-pole)	30 208 V (3-pole)				
9.0	PTBA3150009LS	12	4	33.75 (85.7)	22.13 (56.2)	7.63 (19.4)	255 (116.0)
15.0	PTBA3150015LS	12	4	35.13 (89.2)	22.13 (56.2)	12.38 (31.4)	385 (175.0)
22.5	PTBA3150022LS	18	6	38.25 (97.2)	30.25 (76.8)	13.38 (34.0)	535 (243.0)
30.0	PTBA3150030LS	24	8	43.75 (111.1)	33.00 (83.8)	13.75 (34.9)	680 (308.0)

① The number of secondary circuits shown is only a representation of circuits. Please contact the factory for exact number of secondary circuits available.

304 STAINLESS STEEL/ SNAP-IN BREAKERS

480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz

Three Phase

kVA	Catalog Number	Secondary Maximum Current Output ①		Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)
		120 V (1-pole)	208 V (3-pole)				
9.0	PTBA3150009SS	12	4	33.75 (85.7)	22.13 (56.2)	7.63 (19.4)	255 (116.0)
15.0	PTBA3150015SS	12	4	35.13 (89.2)	22.13 (56.2)	12.38 (31.4)	385 (175.0)
22.5	PTBA3150022SS	18	6	38.25 (97.2)	30.25 (76.8)	13.38 (34.0)	535 (243.0)
30.0	PTBA3150030SS	24	8	43.75 (111.1)	33.00 (83.8)	13.75 (34.9)	680 (308.0)

① The number of secondary circuits shown is only a representation of circuits. Please contact the factory for exact number of secondary circuits available.

SNAP-IN BREAKERS

480 VOLTS DELTA to 208Y/120 VOLTS

Circuit Breaker Data

kVA	480 Volts primary breakers	208Y/120 Volts secondary main	Maximum Rating of Secondary Breakers
9.0	ED43B025L (25A)	Q330 (30A)	25 amps
15.0	ED43B040L (40A)	Q350 (50A)	40 amps
22.5	ED43B070L (70A)	Q370 (70A)	60 amps
30.0	ED43B090L (90A)	Q3100 (100A)	80 amps