



**BOLT-IN BREAKERS**  
**480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz**

Three Phase

kVA	Catalog Number	Secondary Maximum Circuit ①		Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)
		10 120 V (1-pole)	30 208 V (3-pole)				
9.0	PTBB3150009LS	15	7	33.75 (85.7)	22.13 (56.2)	7.63 (19.4)	255 (116.0)
15.0	PTBB3150015LS	15	7	35.13 (89.2)	22.13 (56.2)	12.38 (31.4)	385 (175.0)
22.5	PTBB3150022LS	27	13	43.75 (111.1)	33.00 (83.8)	13.38 (34.0)	680 (308.0)
30.0	PTBB3150030LS	27	13	43.75 (111.1)	33.00 (83.8)	13.75 (34.9)	680 (308.0)

① The number of secondary circuits shown is only a representation of circuits. Please contact the factory for exact number of secondary circuits available.

**304 STAINLESS STEEL/ BOLT-IN BREAKERS**  
**480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz**

Three Phase

kVA	Catalog Number	Secondary Maximum Current Output ①		Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)
		120 V (1-pole)	208 V (3-pole)				
9.0	PTBB3150009SS	15	7	33.75 (85.7)	22.13 (56.2)	7.63 (19.4)	255 (116.0)
15.0	PTBB3150015SS	15	7	35.13 (89.2)	22.13 (56.2)	12.38 (31.4)	385 (175.0)
22.5	PTBB3150022SS	27	13	43.75 (111.1)	33.00 (83.8)	13.75 (34.9)	535 (243.0)
30.0	PTBB3150030SS	27	13	43.75 (111.1)	33.00 (83.8)	13.75 (34.9)	680 (308.0)

① The number of secondary circuits shown is only a representation of circuits. Please contact the factory for exact number of secondary circuits available.

**BOLT-IN BREAKERS**  
**480 VOLTS DELTA to 208Y/120 VOLTS**      **Circuit Breaker Data**

kVA	480 Volts primary breakers	208Y/120 Volts secondary main	Maximum Rating of Secondary Breakers
9.0	ED43B025L (25A)	B330H (30A)	25 amps
15.0	ED43B040L (40A)	B350H (50A)	40 amps
22.5	ED43B070L (70A)	B370H (70A)	60 amps
30.0	ED43B090L (90A)	B3100 (100A)	80 amps

