



440 DELTA PRIMARY VOLTS — 220Y/127 SECONDARY VOLTS — 3Ø, 50 Hz

| kVA | Catalog Number | Height (Inches)(Cm.) | Width (Inches)(Cm.) | Depth (Inches)(Cm.) | Weight (Lbs.)(Kg.) | Mounting Type (Wall)(Floor) | Knockouts (Inches)(Cm.) | Weather Shield | Wiring Diagrams | Design Figures |
|------|----------------|----------------------|---------------------|---------------------|--------------------|-----------------------------|-------------------------|----------------|-----------------|----------------|
| 10.0 | TF220105S | 18.90 (48.0) | 20.30 (51.6) | 9.00 (22.9) | 245 (111.1) | F ① | NA | NA | 73 | I |
| 15.0 | TF220155S | 25.50 (64.8) | 24.40 (62.0) | 19.40 (49.3) | 291 (132.0) | F ① | NA | WSA1 | 73 | E |
| 25.0 | TF220255S | 25.50 (64.8) | 24.40 (62.0) | 19.40 (49.3) | 375 (170.1) | F ① | NA | WSA1 | 73 | E |
| 50.0 | TF220505S | 29.41 (74.7) | 28.15 (71.5) | 22.37 (56.8) | 437 (198.2) | F ① | NA | WSA2 | 73 | E |

① Wall mounting brackets are available for these sizes, refer to page 41.

480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — MAY BE USED ON A 4 WIRE 480Y/277 VOLTS SUPPLY— 3Ø, 60 Hz DOE/NRCAN 2019 Compliant

| kVA | Catalog Number | Height (Inches)(Cm.) | Width (Inches)(Cm.) | Depth (Inches)(Cm.) | Weight (Lbs.)(Kg.) | Mounting Type (Wall)(Floor) | Knockouts (Inches)(Cm.) | Optional Electrostatic Shield | Wiring Diagrams | Design Figures |
|--------|----------------|----------------------|---------------------|---------------------|--------------------|-----------------------------|-------------------------|-------------------------------|-----------------|----------------|
| 3.0 | T2A533081S | 10.38 (26.4) | 12.37 (31.4) | 7.47 (19.0) | 75 (34.0) | W | 0.75-1.25 (1.9-3.2) | STD. | 21 | F |
| 6.0 | T2A533091S | 11.83 (30.0) | 14.17 (36.0) | 8.82 (22.4) | 140 (63.5) | W | 0.75-1.25 (1.9-3.2) | STD. | 21 | F |
| 9.0 | T2A533101S | 14.03 (36.0) | 17.77 (45.1) | 11.52 (29.3) | 180 (81.6) | W | 0.75-1.25 (1.9-3.2) | STD. | 21 | F |
| 15.0 | T3533111S | 18.86 (48.0) | 20.30 (51.6) | 9.03 (22.9) | 250 (113.0) | F ① | NA | STD. | 21 | I |
| 15.0 | T3015K0013B | 25.50 (64.8) | 24.39 (61.9) | 19.37 (49.2) | 300 (136.0) | F ① | NA | YES ② | 22 | E |
| 30.0 | T3030K0013B | 25.50 (64.8) | 24.39 (61.9) | 19.37 (49.2) | 360 (163.2) | F ① | NA | YES ② | 22 | E |
| 45.0 | T3045K0013B | 25.50 (64.8) | 24.39 (61.9) | 19.37 (49.2) | 500 (226.8) | F ① | NA | YES ② | 22 | E |
| 75.0 | T3075K0013B | 29.41 (74.7) | 28.15 (71.5) | 22.37 (56.8) | 600 (272.2) | F ① | NA | YES ② | 22 | E |
| 112.5 | T3112K0013B | 35.47 (90.1) | 31.90 (81.0) | 26.88 (68.2) | 938 (425.5) | F | NA | YES ② | 22 | E |
| 150.0 | T3150K0013B | 41.52 (105.4) | 32.90 (83.5) | 29.87 (75.9) | 1213 (550.2) | F | NA | YES ② | 22 | E |
| 225.0 | T3225K0013B | 41.52 (105.4) | 32.90 (83.5) | 29.87 (75.9) | 1500 (680.4) | F | NA | YES ② | 22 | E |
| 300.0 | T3300K0013B | 45.60 (115.8) | 39.50 (100.3) | 35.50 (90.1) | 1938 (879.0) | F | NA | YES ② | 22 | E |
| 500.0 | T3500K0013B | 57.80 (147.0) | 45.60 (115.8) | 41.50 (105.4) | 3100 (1406.1) | F | NA | YES ② | 22 | G |
| 750.0 | T3750K0013B | 62.80 (159.5) | 54.00 (137.1) | 41.50 (105.4) | 4500 (2041.1) | F | NA | YES ② | 22 | G |
| 1000.0 | T3001M0012B | 62.80 (159.5) | 54.00 (137.1) | 41.50 (105.4) | 5375 (2438.0) | F | NA | YES ② | 80 | G |

① Wall mounting brackets are available for these sizes, refer to page 41.

② Add "S" to part number

