



### 240 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz — DOE/NRCAN 2019 Compliant

kVA	Catalog Number	Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)	Mounting Type (Wall)(Floor)	Knockouts (Inches)(Cm.)	Optional Electrostatic Shield	Wiring Diagrams	Design Figures
9.0	T2A533601S	14.03 (36.0)	17.77 (45.1)	11.52 (29.3)	180 (81.6)	W	0.75-1.25 (1.9-3.2)	STD.	18	F
15.0	T3533611S	18.86 (48.0)	20.30 (51.6)	9.03 (23.0)	250 (113.0)	F ①	NA	STD.	18	I
15.0	T3015K0044B	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	300 (136.0)	F ①	NA	YES ②	19	E
30.0	T3030K0044B	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	360 (163.2)	F ①	NA	YES ②	19	E
45.0	T3045K0044B	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	438 (198.6)	F ①	NA	YES ②	19	E
75.0	T3075K0044B	29.41 (74.7)	28.15 (71.5)	22.37 (56.8)	600 (272.2)	F ①	NA	YES ②	19	E
112.5	T3112K0044B	35.47 (90.1)	31.90 (81.0)	26.88 (68.2)	870 (394.6)	F	NA	YES ②	19	E
150.0	T3150K0044B	41.52 (105.4)	32.90 (83.5)	29.87 (75.9)	1223 (554.7)	F	NA	YES ②	19	E
225.0	T3225K0044B	41.52 (105.4)	32.90 (83.5)	29.87 (75.9)	1500 (680.4)	F	NA	YES ②	19	E

① Wall mounting brackets are available for these sizes, refer to page 41.

② Add "S" to part number

### 240 DELTA PRIMARY VOLTS — 480Y/277 SECONDARY VOLTS — 3Ø, 60 Hz — DOE/NRCAN 2019 Compliant

kVA	Catalog Number	Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)	Mounting Type (Wall)(Floor)	Knockouts (Inches)(Cm.)	Optional Electrostatic Shield	Wiring Diagrams	Design Figures
15.0	T3796931S	18.90 (48.0)	20.30 (51.6)	9.00 (22.9)	245 (111.1)	F ①	NA	STD.	70	I
15.0	T3015K0074B	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	300 (136.0)	F ①	NA	YES ②	71	E
30.0	T3030K0074B	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	360 (163.2)	F ①	NA	YES ②	71	E
45.0	T3045K0074B	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	475 (215.5)	F ①	NA	YES ②	71	E
75.0	T3075K0074B	29.41 (74.7)	28.15 (71.5)	22.37 (56.8)	600 (272.2)	F ①	NA	YES ②	71	E
112.5	T3112K0074B	35.47 (90.1)	31.90 (81.0)	26.88 (68.2)	859 (389.6)	F	NA	YES ②	71	E
150.0	T3150K0074B	41.52 (105.4)	32.90 (83.5)	29.87 (75.9)	1216 (551.6)	F	NA	YES ②	71	E

① Wall mounting brackets are available for these sizes, refer to page 41.

② Add "S" to part number

### 380 DELTA PRIMARY VOLTS — 220Y/127 SECONDARY VOLTS — 3Ø, 50 Hz

kVA	Catalog Number	Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)	Mounting Type (Wall)(Floor)	Knockouts (Inches)(Cm.)	Weather Shield	Wiring Diagrams	Design Figures
15.0	T3795511S	20.80 (52.8)	20.90 (53.1)	10.20 (25.9)	435 (197.3)	F	NA	NA	24	I
30.0	T2A795523S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	365 (165.6)	F ①	NA	WSA1	20	E
45.0	T2A795533S	29.41 (74.7)	28.15 (71.5)	22.37 (56.8)	468 (212.3)	F ①	NA	WSA2	20	E
75.0	T2A795543S	35.47 (90.1)	31.90 (80.0)	26.88 (68.3)	693 (314.3)	F	NA	WSA3	20	E
112.5	T2A795553S	41.52 (105.4)	32.90 (83.5)	29.87 (75.9)	970 (440.0)	F	NA	WSA4	20	E

① Wall mounting brackets are available for these sizes, refer to page 41.

All Wiring Diagrams begin on page 35.