

Dune[®] Compact Balances

Streamlined design for basic weighing in the lab, classroom or field



Features

- High-contrast display is easily visible from a distance
- Color-coded keys facilitate quick recognition of the most frequently used buttons
- Lightweight design simplifies transport and portability
- Overload protection helps prevent damage to internal components
- Sealed keypad protects against dirt and spills
- Large platform removes easily for speedy cleaning
- Operates with AC adapter (included) or batteries (not included)
- Auto power-off to save energy
- Zero-tracking feature ensures display returns to zero reading



General Specifications

- Weighing units: g, lb*, oz
 - Power supply: 6 x AA Batteries, 12VDC 500mA adapter (optional)
 - Display: LCD with 0.6" / 15mm-high digits
 - Calibration: External
 - Housing: ABS Plastic
 - Operating temperature: 0° to 40°C / 32° to 104°F
- *lb not available in DCT 201

Applications

- Weighing

WARRANTY
12
MONTHS

Product Details

Model	Capacity	Readability	Pan Size	Shipping Weight	Shipping Dimensions	Price
DCT 201	200g	0.1g	5.7"x5.7" / 145x145mm	3lb / 1.36kg	4"x12"x8" / 102x305x203mm	\$105.00
DCT 2000	2000g	1g	5.7"x5.7" / 145x145mm	3lb / 1.36kg	4"x12"x8" / 102x305x203mm	\$105.00
DCT 5000	5000g	2g	5.7"x5.7" / 145x145mm	3lb / 1.36kg	4"x12"x8" / 102x305x203mm	\$110.00

Accessories

Item number	Description	Price
700660290	Calibration certificate.....	\$85.00
700100012	F1 200g Calibration Weight.....	\$105.00
700100010	F1 2kg Calibration Weight.....	\$295.00
700100377	ASTM 4 200g Calibration Weight.....	\$80.00
700100379	ASTM 4 1kg Calibration Weight.....	\$185.00
700100192	ASTM 4 2kg Calibration Weight.....	\$325.00