

## 10" In-Line Steel Axial Fans



SVF-10E

10" to 8" Duct Adapters Supplied with Fan for Intake and Exhaust



SVF-10EXP



Dual grounding lugs to remove static electricity

SVF-10X220



Standard Models	Model No.	Free Air	25' 1-90° Bend	25' 2-90° Bends
10" Blower	SVF-10E	1390 CFM	870 CFM	858 CFM
10" Blower (50 Hz)	SVF-10AC50	1158 CFM	725 CFM	715 CFM
Explosion-Proof Models	Model No.	Free Air	25' 1-90° Bend	25' 2-90° Bends
10" EXP Blower	SVF-10EXP	1390 CFM	870 CFM	858 CFM
10" EXP Blower (50 Hz)	SVF-10X220	1158 CFM	725 CFM	715 CFM

The 10" in-line axial fan has been designed to be used as a stand alone fan or attached in series to run long lengths of ventilation duct. Intake and exhaust flanges allow for either 8" or 10" duct to be attached to either end of the blower to achieve positive or negative ventilation. Made of lightweight steel, the blower is available in standard or explosion-proof electric versions. The conductive explosion-proof fan, SVF-10EXP, is certified by CSA for sale in the US and Canada. Model SVF-10X220 is ATEX and IECEx certified by Intertek for use in Zone 1 or Zone 2 hazardous locations.

### 10" In-Line Steel Axial Fans

Item No.	Description
<b>Non-Hazardous Locations</b>	
SVF-10E	10" Electric in-line fan, continuous duty, 1/3 HP, 115 VAC, 60 Hz, 30 lbs.
SVF-10AC50	10" Electric in-line fan, continuous duty, 1/3 HP, 230 VAC, 50 Hz, 30 lbs.
<b>Hazardous Locations</b>	
SVF-10EXP	10" Explosion-proof electric in-line fan, continuous duty, 1/3 HP, 115 VAC, 1-phase, 60 Hz, plug not included, 38 lbs.
SVF-10X220	10" Explosion-proof electric in-line fan, continuous duty, 1/3 HP, 230 VAC, 50/60 Hz, plug not included, 38 lbs.

Plug sold separately. No additional labor charge for installation prior to shipment.

#### Approved for Hazardous Location Usage:

SVF-10EXP - CSA C/US certified for Classes I and II, Groups C, D, E, F, and G.

SVF-10X220 - ATEX and IECEx certified for II 2 Gc Ex d IIB T6 Gb

### Explosion-Proof Plugs


Item No.	Description
ELAP15231	15 AMP, 125 VAC, EXP plug w/quick wiring (5-15P) USA / Canada
ELAP20231	20 AMP, 125 VAC, EXP plug w/quick wiring (5-20P) USA / Canada
ELAP15232	15 AMP, 250 VAC, EXP plug w/quick wiring (6-15P) International
ELAP20232	20 AMP, 250 VAC, EXP plug w/quick wiring (6-20P) International

No additional labor charge for installation prior to shipment.


### Explosion-Proof Plugs




ELAP15231



ELAP20231



ELAP15232



ELAP20232