

8" Steel Axial Fans & Canister Fans

Our steel axial fan is a rugged, low cost fan with high volume output and medium static pressure. Designed for non-hazardous locations and CSA C/US certified for outdoor use.



8" Electric Axial Fan
SVF-8AC



8" Steel
Axial Canister Fan
SVF-15ACAN

Model	Model No.	Free Air	25' 1-90° Bend	25' 2-90° Bends
AC Blower (60 Hz)	SVF-8AC	1275 CFM	797 CFM	677 CFM
DC Blower (12 VDC)	SVF-8DC	1275 CFM	797 CFM	677 CFM

8" Steel Axial Fans

Item No.	Description
Axial Fans	
SVF-8AC	AC axial fan - 1/3 HP, 115 VAC, 60 Hz CSA C/US Certified. CE Registered. 27 lbs.
SVF-8DC	DC axial fan - 12 VDC, 1/4 HP, 20 amps, with battery clamps. CE Registered. 25 lbs.
Axial Canister Fans	
SVF-15ACAN	SVF-8AC AC fan, canister fan with 15 foot duct installed
SVF-25ACAN	SVF-8AC AC fan, canister with 25 foot duct installed
SVF-15DCAN	SVF-8DC DC fan, canister with 15 foot duct installed
SVF-25DCAN	SVF-8DC DC fan, canister with 25 foot duct installed

See Master Catalog
for Additional Fans &
Ventilation Kits

10" In-Line Steel Axial Fans & Kits

The 10" in-line axial fan is designed as a stand alone fan or can be attached in series to run long lengths of ventilation duct. Intake and exhaust flanges allow for either 8" or 10" duct to be attached to either end of the blower to achieve positive or negative ventilation.

10" In-Line Steel Axial Fans & Kits - Non-Hazardous Locations

Item No.	Description
SVF-10E	10" Electric in-line fan, continuous duty, 1/2 HP, 115 VAC, 60 Hz. CSA C/US Certified. CE Registered. 30 lbs.
SVF-10ECUP	SVF-10E fan, Industrial Saddle Vent®, 6 & 15 foot 8" duct, duct canister, 90° elbow, & universal mount



10" In-Line Steel Axial Fans & Kits - Hazardous Locations

Item No.	Description
SVF-10EXP	10" Explosion-proof electric in-line fan, continuous duty, 1/2 HP, 115 VAC, 1-phase, 60 Hz. CSA C/US Certified. CE Registered. 38 lbs. No plug.
SVF10EXCUP	SVF-10EXP fan, Conductive Saddle Vent®, 6 & 15 foot 8" conductive duct, duct canister, conductive elbow, and universal mount. No plug.

Explosion-proof plug sold separately - See Page 21

Standard Model	Model No.	Free Air	25' 1-90° Bend	25' 2-90° Bends
10" Blower (60 Hz)	SVF-10E	868 CFM	648 CFM	589 CFM
Explosion-Proof Model	Model No.	Free Air	25' 1-90° Bend	25' 2-90° Bends
10" EXP Blower (60 Hz)	SVF-10EXP	994 CFM	738 CFM	678 CFM



SVF-10E

Fans Approved for Hazardous Locations:

SVF-10EXP - CSA C/US certified for Classes I and II, Groups C, D, E, F, and G.

SVF-10X220 - ATEX and IECEx certified for II 2 Gc Ex d IIB T6 Gb

10" to 8" Duct Adapters
Supplied for Intake and Exhaust