

AC HYDRAULIC MINING JACKS



AME International presents AC Hydraulic^{A/S} heavy duty jacks for low clearance machinery in mining and construction industries.

All steel, heavy duty chassis build to fit harsh environments. Large rubber tires allow easy positioning on challenging surfaces. Innovative chassis construction facilitates jack repair and even wheel changing on site. High ground clearance for clearing rail and rough terrain. Multiple position handle for easy tilt back and moving. Handle with dead-man's release for optimum safety during lifting and lowering. Mining jack handle length: 51.2" (130 cm).



Model	Capacity	Min. Height / Max. Height	Total Width	Frame Length	Air Supply	Air Consumption	Ground Clearance	Weight
100-1L	100 tons	17.1" (43.5 cm) / 22.4" (57 cm)	18.3" (46.5 cm)	61" (155 cm)	145 psi	1200 l/min	1.6" (4 cm)	731.9 lbs (332 kg)
150-1L	150 tons	17.1" (43.5 cm) / 22.4" (57 cm)	18.3" (46.5 cm)	61" (155 cm)	145 psi	1200 l/min	1.6" (4 cm)	731.9 lbs (332 kg)
100-1	100 tons	27.6" (70 cm) / 43.3" (110 cm)	27" (68.5 cm)	66" (167.5 cm)	145 psi	1200 l/min	2.6" (6.5 cm)	1049.4 lbs (476 kg)
150-1	150 tons	27.6" (70 cm) / 43.3" (110 cm)	27" (68.5 cm)	66" (167.5 cm)	145 psi	1200 l/min	2.6" (6.5 cm)	1049.4 lbs (476 kg)
100-1H	100 tons	37.4" (95 cm) / 63" (160 cm)	27" (68.5 cm)	66" (167.5 cm)	145 psi	1200 l/min	2.6" (6.5 cm)	1203.7 lbs (546 kg)
150-1H	150 tons	37.4" (95 cm) / 63" (160 cm)	27" (68.5 cm)	66" (167.5 cm)	145 psi	1200 l/min	2.6" (6.5 cm)	1203.7 lbs (546 kg)



FHD100 / FHD200 Extensions

Increases lifting height by 3.9" (10 cm) / 7.9" (20 cm)



SB65 / SB100 / SB150 Locking Rings

SB65: 6.5 cm

Fits: All models

SB100: 10 cm

Fits: 100-1 / 150-1, 100-1H / 150-1H

SB150: 15 cm

Fits: 100-1 / 150-1, 100-1H / 150-1H



BHD Locking Ring Holder

Allows for the locking rings to be stored on the jack (Included in Locking Ring Kit)



HHD Extension Holder

Allows for extensions to be stored on the side of the jack

