

Wrench, Socket, L-type, 6-Point – Cont.

Millimeter (mm)				American Inch (")					
No.	s mm	a mm	l mm	Δ g	No.	s inch	a inch	l inch	Δ lbs.
SL-30	30	75	395	1300	SL-1-3/8	1-3/8	3-1/2	18-1/4	6.17
SL-32	32	80	425	1700	SL-1-7/16	1-7/16	3-1/2	18-1/4	6.17
SL-33	33	80	425	1700	SL-1-1/2	1-1/2	3-1/2	18-1/4	6.17
SL-34	34	80	425	1700	SL-1-9/16	1-9/16	3-25/32	20	7.94
SL-35	35	90	465	2800	SL-1-5/8	1-5/8	3-25/32	20	7.94
SL-36	36	90	465	2800	SL-1-11/16	1-11/16	3-25/32	20	7.94
SL-37	37	90	465	2800	SL-1-3/4	1-3/4	4-1/8	21-3/4	8.82
SL-38	38	90	465	2800	SL-1-13/16	1-13/16	4-1/8	21-3/4	8.82
SL-41	41	95	510	3600	SL-1-7/8	1-7/8	4-1/8	21-3/4	8.82
SL-42	42	95	510	3600	SL-2	2	4-1/2	23-3/4	10.58
SL-46	46	105	555	4000	SL-2-1/16	2-1/16	4-1/2	23-3/4	10.58
SL-47	47	105	555	4000	SL-2-1/8	2-1/8	4-23/32	26	14.11
SL-50	50	115	605	4800	SL-2-3/16	2-3/16	4-23/32	26	14.11
SL-52	52	115	605	4800	SL-2-1/4	2-1/4	4-7/16	28-3/4	18.08
SL-54	54	120	660	6400	SL-2-5/16	2-5/16	4-7/16	28-3/4	18.08
SL-55	55	120	660	6400	SL-2-3/8	2-3/8	4-7/16	28-3/4	18.08
SL-56	56	120	660	6400	SL-2-7/16	2-7/16	4-7/16	28-3/4	18.08
SL-58	58	140	730	8200	SL-2-1/2	2-1/2	5-29/32	31-1/2	22.93
SL-60	60	140	730	8200	SL-2-9/16	2-9/16	5-29/32	31-1/2	22.93
SL-63	63	140	730	8200	SL-2-5/8	2-5/8	5-29/32	31-1/2	22.93
SL-65	65	150	800	10400	SL-2-3/4	2-3/4	5-29/32	31-1/2	22.93
SL-67	67	150	800	10400	SL-2-13/16	2-13/16	6-17/32	34-1/2	31.09
SL-70	70	150	800	10400	SL-2-15/16	2-15/16	6-17/32	34-1/2	31.09
SL-71	71	150	800	10400	SL-3	3	6-17/32	34-1/2	31.09
SL-75	75	166	880	14100	SL-3-1/8	3-1/8	6-17/32	34-1/2	31.09
SL-77	77	166	880	14100	SL-3-1/4	3-1/4	6-17/32	34-1/2	31.09
SL-80	80	166	880	14100					
SL-82	82	166	880	14100					

Wrenches

Wrench, Adjustable End

Clé à molette

Llave de Cabeza Ajustable



No.	s max mm	l mm	Δ g	s max inch	l inch	Δ lbs.
W-70	24	150	100	15/16	6	.22
W-71	29	200	200	1-1/8	8	.44
W-72	33	255	313	1-5/16	10	.69
W-73	38	305	567	1-1/2	12	1.25
W-74	43	380	1275	1-11/16	15	2.81

Wrench, Box End, 12-Point⁶ (DIN 3111)

Clé fermée, 12 pans

Llave de Cajón Sencilla, 12-Puntos



Millimeter (mm)				American Inch (")			
No.	s mm	l mm	Δ g	No.	s inch	l inch	Δ lbs.
4400	14	155	90	4600	1/2	6	.20
4402	15	155	90	4602	9/16	6	.20
4404	16	155	90	4604	19/32	6	.20
4406	17	155	90	4606	5/8	6	.20
4408	18	190	160	4608	11/16	6	.20
4410	19	190	160	4610	3/4	7-1/2	.35
4412	20	190	160	4612	25/32	7-1/2	.35
4414	21	190	160	4614	13/16	7-1/2	.35
4416	22	190	160	4616	7/8	7-1/2	.35
4418	23	190	160	4618	15/16	9	.62
4420	24	230	280	4620	31/32	9	.62
4422	25	230	280	4622	1	9	.62
4424	26	230	280	4624	1-1/16	9	.62
4426	27	230	280	4626	1-1/8	10-1/2	.88
4428	28	230	280	4628	1-3/16	10 1/2	.88
4430	29	230	280	4630	1-1/4	10-1/2	.88
4432	30	265	400	4632	1-5/16	13	1.65
4434	32	265	400	4634	1-3/8	13	1.65
4436	33	265	400	4636	1-7/16	13	1.65
4438	34	330	750	4638	1-1/2	13	1.65
4440	35	330	750	4640	1-9/16	13	1.65
4442	36	330	750	4642	1-5/8	13	1.65
4444	37	330	750	4644	1-11/16	13	1.65
4446	38	330	750	4646	1-3/4	15-3/4	3.09
4448	41	330	750	4648	1-13/16	15-3/4	3.09
4450	42	330	750	4650	1-7/8	15-3/4	3.09
4452	46	400	1400	4652	2	15-3/4	3.09
4454	47	400	1400	4654	2-1/16	15-3/4	3.09
4456	50	400	1400	4656	2-1/8	18-3/4	4.19
4458	52	400	1400	4658	2-3/16	18-3/4	4.19
4460	54	400	1400	4660	2-1/4	18-3/4	4.19
4462	55	475	1900	4662	2-5/16	18-3/4	4.19
4464	56	475	1900	4664	2-3/8	18-3/4	4.19
4466	58	475	1900	4666	2-7/16	18-3/4	4.19
4468	60	475	1900	4668	2-1/2	21-3/4	6.39
4470	63	475	1900	4670	2-9/16	21-3/4	6.39
4472	65	555	2900	4672	2-3/4	21-3/4	6.39