

### MODEL 102T/102T-LF NPT END NON-RISING STEM GATE VALVE



#### FEATURES

- Threaded Bonnet
- Solid Bronze Disc
- 200 CWP
- 125 SWP
- Max Temp: 406°F
- Lead Free Option (NSF/ANSI/CAN 61 & NSF/ANSI/CAN 372)

#### STANDARDS

- MSS SP-80 Standard
- MSS SP-139 Lead Free Option (CWP only)
- ASTM B62 Bronze (ASTM B584-C89836 Lead Free)

#### APPROVALS

- CRN OC14667



PART NUMBER	LF PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
30-031-01	30LF-031-01	1/4	1.76	3.29	0.74
30-032-01	30LF-032-01	3/8	1.76	3.29	0.71
30-033-01	30LF-033-01	1/2	2.03	3.56	0.85
30-034-01	30LF-034-01	3/4	2.07	4.05	1.19
30-035-01	30LF-035-01	1	2.45	4.55	1.98
30-036-01	30LF-036-01	1-1/4	2.63	5.14	2.80
30-037-01	30LF-037-01	1-1/2	2.88	6.02	3.95
30-038-01	30LF-038-01	2	3.06	7.09	5.88
30-039-01	30LF-039-01	2-1/2	4.13	9.11	12.19
30-030-01	30LF-030-01	3	4.48	12.61	16.84

Length is measured from end-to-end.  
Height is measured from centerline to top of wheel in full open position.

### MODEL 102T-K NPT END NON-RISING STEM IRRIGATION GATE VALVE

#### FEATURES

- Threaded Bonnet
- Solid Bronze Disc
- Bronze Cross-Handle (Irrigation)
- 200 CWP
- 125 SWP
- Max Temp: 406°F
- SS Stem Nut

#### STANDARDS

- MSS SP-80 Standard
- ASTM B62 Bronze

#### APPROVALS

- CRN OC14667



PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
30-033-01K	1/2	2.03	3.56	0.85
30-034-01K	3/4	2.07	4.05	1.19
30-035-01K	1	2.45	4.55	1.98
30-036-01K	1-1/4	2.63	5.14	2.80
30-037-01K	1-1/2	2.88	6.02	3.95
30-038-01K	2	3.06	7.09	5.88
30-039-01K	2-1/2	4.13	9.11	12.19
30-030-01K	3	4.48	12.61	16.84

Length is measured from end-to-end.  
Height is measured from centerline to top of wheel in full open position.  
30LF-03X-01K available upon request.

### MODEL 103T NPT END RISING STEM GATE VALVE

#### FEATURES

- Threaded Bonnet
- Solid Bronze Disc
- 200 CWP
- 125 SWP
- Max. Temp: 406°F

#### STANDARDS

- MSS SP-80 Standard
- ASTM B62 Bronze

#### APPROVALS

- CRN OC14667



PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
30-051-01	1/4	1.76	4.57	0.90
30-052-01	3/8	1.76	4.51	0.86
30-053-01	1/2	2.03	4.85	1.07
30-054-01	3/4	2.07	5.71	1.43
30-055-01	1	2.45	6.71	2.44
30-056-01	1-1/4	2.63	8.10	3.71
30-057-01	1-1/2	2.88	9.08	4.89
30-058-01	2	3.06	11.28	7.53
30-059-01	2-1/2	4.96	14.58	15.33
30-050-01	3	4.48	19.07	19.56

Length is measured from end-to-end.  
Height is measured from centerline to top of wheel in full open position.