

### MODEL 120S/120S-LF SOLDER END GLOBE VALVE



#### FEATURES

- Threaded Bonnet
- PTFE Disc
- 200 CWP
- Max. Temp: 406°F
- Lead Free Option (NSF/ANSI/CAN 61 & NSF/ANSI/CAN 372)

#### STANDARDS

- MSS SP-80 Standard
- ASTM B62 Bronze (ASTM B584-C89836 Lead Free)

#### APPROVALS

- CRN OC14667



PART NUMBER	LF PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
33-143-01	33LF-143-01	1/2	2.97	3.47	1.00
33-144-01	33LF-144-01	3/4	3.83	4.75	1.90
33-145-01	33LF-145-01	1	4.57	5.40	2.80
33-146-01	33LF-146-01	1-1/4	5.95	7.80	7.30
33-147-01	33LF-147-01	1-1/2	5.95	7.80	6.80
33-148-01	33LF-148-01	2	7.18	8.43	10.60

Length is measured from end-to-end.  
Height is measured from centerline to top of wheel in full open position.

### MODEL 120T/120T-LF CLASS 125 NPT GLOBE VALVE



#### FEATURES

- Threaded Bonnet
- PTFE Disc
- 200 CWP
- 125 SWP
- Max. Temp: 406°F
- Lead Free Option (NSF/ANSI/CAN 61 & NSF/ANSI/CAN 372)

#### STANDARDS

- SS SP-80 Standard
- ASTM B62 Bronze (ASTM B584-C89836 Lead Free)

#### APPROVALS

- CRN OC14667



PART NUMBER	LF PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
33-132-01	33LF-132-01	3/8	2.39	3.37	1.00
33-133-01	33LF-133-01	1/2	2.70	3.47	1.10
33-134-01	33LF-134-01	3/4	3.20	4.75	1.90
33-135-01	33LF-135-01	1	3.75	5.40	3.00
33-136-01	33LF-136-01	1-1/4	4.74	7.78	7.30
33-137-01	33LF-137-01	1-1/2	4.74	7.78	7.00
33-138-01	33LF-138-01	2	5.72	8.43	10.70

Length is measured from end-to-end.  
Height is measured from centerline to top of wheel in full open position.

### MODEL 121T/121T-LF CLASS 125 NPT GLOBE VALVE



#### FEATURES

- Threaded Bonnet
- Solid Bronze Disc
- 200 CWP
- 125 SWP
- Max. Temp: 406°F
- Lead Free Option (NSF/ANSI/CAN 61 & NSF/ANSI/CAN 372)

#### STANDARDS

- MSS SP-80 Standard
- MSS SP-139 Lead Free Option (CWP only)
- ASTM B62 Bronze (ASTM B584-C89836 Lead Free)

#### APPROVALS

- CRN OC14667



PART NUMBER	LF PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
33-161-01	33LF-161-01	1/4	2.39	3.46	1.00
33-162-01	33LF-162-01	3/8	2.39	3.46	1.00
33-163-01	33LF-163-01	1/2	2.70	3.56	1.10
33-164-01	33LF-164-01	3/4	3.20	4.75	1.90
33-165-01	33LF-165-01	1	3.75	5.40	3.00
33-166-01	33LF-166-01	1-1/4	4.74	7.78	7.30
33-167-01	33LF-167-01	1-1/2	4.74	7.78	7.00
33-168-01	33LF-168-01	2	5.72	8.43	11.00

Length is measured from end-to-end.  
Height is measured from centerline to top of wheel in full open position.