


59V SERIES "MINI" STRAINER



The body of the 59-V is corrosion-resistant solid cast bronze, ASTM B-584. The removable clean-out cap is solid brass, ASTM B-16. Standard screens are made of 304 stainless steel. NOT INTENDED FOR POTABLE WATER

FEATURES

- C_v Factor 1.42 GPM
- **Proudly Made in USA**


PERFORMANCE RATING

- Working Pressure:
CWP: 400 psi
SWP: 125 psi
- Maximum Temperature: 350° F

DIMENSIONS

PART NUMBER	SIZE (IN.)	DIMENSIONS (IN.)		WT./100	SCREEN MESH
		A	B		
59V-001-01	1/4 NPT	2.00	1.31	29.7	50
59V-001-H1	1/4 NPT	2.00	1.31	29.7	100

YSS (612) SERIES STAINLESS STEEL WYE STRAINER



Sturdy and compact with corrosion-resistant stainless steel bodies and stainless steel screens.

FEATURES

- Body is ASTM 316 Stainless Steel Grade CF8M
- 20 Mesh Screen
- Gasket 304 SS/Graphite
- Screen cover is NPT tapped for Customer Supplied Plug or Blow-Off Valve
- **Proudly Made in USA**

PERFORMANCE RATING

- Working Pressure:
CWP: 1480 psi
SWP: 600 psi
- Maximum Temperature: 488° F

DIMENSIONS

PART NUMBER	SIZE (IN.)	DIMENSIONS (IN.)		BLOW-OFF NPT	WT. (LB.)	NET SCREEN AREA (IN. ²)
		A	B			
612-033-A1	1/2	3.38	2.75	3/8	2	5.4
612-034-A1	3/4	4.44	3.63	3/8	3.75	8.7
612-035-A1	1	4.88	3.75	1/2	4	12.7