

MODEL 910WB

CLASS 125 WAFER CHECK - NITRILE (BUNA-N)



FEATURES

- Compatible with ANSI 125# & 150# Flanges
- Full Port
- Minimal Pressure Drop
- Light Weight
- Spring Assisted Closing for Quicker Response
- Apollo International™

PERFORMANCE RATING

- 250 psi (17.2 Bar) Non-Shock Cold Working Pressure
- Maximum Temperature to 180°F (82°C)
- **Not For Steam Use**

APPROVALS (LEAD FREE ONLY)

- NSF/ANSI/CAN 61 - Water Quality
- NSF/ANSI/CAN 372 - Lead Free

PART NUMBER	LF PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
6WC-108-N1	6WC-108-N1-LF	2	2.12	4.00	5.0
-	6WC-109-N1-LF	2-1/2	2.38	4.75	7.0
-	6WC-100-N1-LF	3	2.62	5.25	10.0
-	6WC-10A-N1-LF	4	2.62	6.75	12.0
-	6WC-10B-N1-LF	5	3.25	7.50	15.0
-	6WC-10C-N1-LF	6	3.75	8.50	22.0
-	6WC-10E-N1-LF	8	5.00	11.00	35.0
6WC-10G-N1	6WC-10G-N1-LF	10	5.50	13.25	66.0
-	6WC-10H-N1-LF	12	7.12	16.00	108

MODEL 910WE

CLASS 125 WAFER CHECK - EPDM



FEATURES

- Compatible with ANSI 125# & 150# Flanges
- Full Port
- Minimal Pressure Drop
- Light Weight
- Spring Assisted Closing for Quicker Response
- Apollo International™

PERFORMANCE RATING

- Cold Working Pressure: 200 psi (13.8 Bar) at 100°F
- Temperature Range: -20°F to 180°F
- **Not For Steam Use**

APPROVALS

- CSA B51

APPROVALS (LEAD FREE ONLY)

- NSF/ANSI/CAN 61 - Water Quality
- NSF/ANSI/CAN 372 - Lead Free

PART NUMBER	LF PART NUMBER	NPS	LENGTH (IN.)	HEIGHT (IN.)	WEIGHT (LB.)
6WC-108-E1	6WC-108-E1-LF	2	2.12	4.00	5.0
-	6WC-109-E1-LF	2-1/2	2.38	4.75	7.0
-	6WC-100-E1-LF	3	2.62	5.25	10.0
-	6WC-10A-E1-LF	4	2.62	6.75	12.0
6WC-10B-E1	6WC-10B-E1-LF	5	3.25	7.50	15.0
-	6WC-10C-E1-LF	6	3.75	8.50	22.0
-	6WC-10E-E1-LF	8	5.00	11.00	35.0
-	6WC-10G-E1-LF	10	5.50	13.25	66.0
-	6WC-10H-E1-LF	12	7.12	16.00	108