










A-51™ Incandescent Factory Sealed Luminaires

For Group C and D Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS® for use with Threaded Metal Conduit.

NEC/CEC — For Group C and D:
 Class I, Division 1 and 2, Groups C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III

Type	Fixture Size	Catalog Number								
Standard Dome										
 <p>406.4 (16.00)</p> <p>Porcelain</p>	 <p>406.4 (16.00)</p> <p>Polyester</p>	(Not for use with short brackets)								
		60-100 W (AAU-1N) 150-300 W (AAU-15N) 200-300 W (AAU-2NS)		<table border="1"> <thead> <tr> <th>Porcelain</th> <th>Polyester</th> </tr> </thead> <tbody> <tr> <td>AARW-15ST</td> <td>—</td> </tr> <tr> <td>AARW-15ST</td> <td>—</td> </tr> <tr> <td>AARW-2ST</td> <td>AARP-2ST</td> </tr> </tbody> </table>	Porcelain	Polyester	AARW-15ST	—	AARW-15ST	—
Porcelain	Polyester									
AARW-15ST	—									
AARW-15ST	—									
AARW-2ST	AARP-2ST									
30° Angle										
 <p>304.8 (12.00)</p> <p>Porcelain</p>	 <p>304.8 (12.00)</p> <p>Polyester</p>	60-100 W (AAU-1N) 150-300 W (AAU-15N) 200-300 W (AAU-2NS)								
		<table border="1"> <tbody> <tr> <td>AARW-15AN</td> <td>—</td> </tr> <tr> <td>AARW-15AN</td> <td>—</td> </tr> <tr> <td>AARW-2AN</td> <td>AARP-2AN</td> </tr> </tbody> </table>		AARW-15AN	—	AARW-15AN	—	AARW-2AN	AARP-2AN	
AARW-15AN	—									
AARW-15AN	—									
AARW-2AN	AARP-2AN									
Colored Glass Globes										
	Amber									
	60-100 W (AAU-1N)		AAGL-1A							
	150-300 W (AAU-15N)		AAGL-1A							
	200-300 W (AAU-2NS)		AAGL-2A							
	Green									
	60-100 W (AAU-1N)		AAGL-1G							
	150-300 W (AAU-15N)		AAGL-1G							
	200-300 W (AAU-2NS)		AAGL-2G							
	Red									
60-100 W (AAU-1N)		AAGL-1R								
150-300 W (AAU-15N)		AAGL-1R								
200-300 W (AAU-2NS)		AAGL-2R								
Replacement Socket										
 <p>AASP-22</p>	 <p>AASP-44</p>	60-100 W (AAU-1N) — Medium Base 150-300 W (AAU-15N) — Medium Base 200-300 W (AAU-2NS) — Medium Base								
		AASP-11								
		AASP-22								
		AASP-44								
Connection Block										
		Fits A-51 Mounting Hoods 60-300 W								
		VPT-7								
Globe Gaskets — Fiber and Aluminum										
		Requires one of each 60-300 W (AAU-1N and AAU-15N) 200-300 W (AAU-2NS)								
		<table border="1"> <thead> <tr> <th>Fiber</th> <th>Aluminum</th> </tr> </thead> <tbody> <tr> <td>AASP-15V</td> <td>AASP-15A</td> </tr> <tr> <td>AASP-2V</td> <td>AASP-2A</td> </tr> </tbody> </table>	Fiber	Aluminum	AASP-15V	AASP-15A	AASP-2V	AASP-2A		
Fiber	Aluminum									
AASP-15V	AASP-15A									
AASP-2V	AASP-2A									

Appleton®

INCANDESCENT/AREA: NEC/CEC EXPLOSIONPROOF