









# A-51™ Incandescent Factory Sealed Luminaires

## For Group A and B Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS® for use with Threaded Metal Conduit.

NEC/CEC — For Group A and B:  
 Class I, Division 1 and 2, Groups A, B, C, D  
 Class II, Division 1 and 2, Groups E, F, G  
 Class III

### Mounting Hoods

	Type	Hub Size (Inches)	Catalog Number
<b>Pendant</b>		One Hub, Rigid or Flexible Mounting	1/2 <b>AAP-50</b> ① 3/4 <b>AAP-75</b> ①
		<b>Ceiling</b>	
<b>15° Short Bracket</b>			
			<b>Description</b>
<b>Fixture Units</b>		60-200 W PS-25	<b>AAUA-15</b>
		200-300 W PS-30	<b>AAUA-2</b>
<b>Globe and Ring Assembly</b>		60-200 W (AAUA-15)	<b>AAGLA-15</b>
		200-300 W (AAUA-2)	<b>AAGLA-2</b>
<b>Aluminum Guards</b>		60-200 W (AAUA-15)	<b>AAGUA-15</b>
		200-300 W (AAUA-2)	<b>AAGU-2</b>
<b>Medium Base Lamp Socket</b>		60-200 W (AAUA-15)	<b>AASPA-15</b>
		200-300 W (AAUA-2)	<b>AASPA-22</b>
<b>Connection Block</b>		Fits all A-51 and AA-51 mounting hoods 60-300 W	<b>VPT-7</b>

① Group A pendant mount only.