AL Ball and Cushion Flexible Fixture HangersUNILETS® for Use with Threaded Rigid Metal Conduit and IMC. Ball Joint Permits 20° Swing.

NEC: Listed for Ordinary (Unclassified) Locations

	Conduit Size (Inches)	Fixture Stem Size (Inches)	Support Weight kg (lbs)	Catalog Number
ALA — Ball Hanger				
	1/2	1/2	112.5 (250)	ALA50-B
	3/4	1/2		ALA7550-B
	3/4	3/4	112.5 (250)	ALA75-B
ALA — Cushion Hanger — Furnish	ed with a 3/4" to 1/2 re	educer for 1/2" stem	s	
	1/2	3/4 or 1/2	1 4 to E 4 (0 to 10)	ALA50-12
0 0	3/4	3/4 or 1/2	1.4 to 5.4 (3 to 12)	ALA7575-12
	1/2	3/4 or 1/2	E 4 to 01 C (10 to 40)	ALA50-48
	3/4	3/4 or 1/2	5.4 to 21.6 (12 to 48)	ALA7575-48
	1/2	3/4 or 1/2	04.0454.0 (40.1400)	ALA50-120
	3/4	3/4 or 1/2	21.6 to 54.0 (48 to 120)	ALA7575-120
ALC — Ball Hanger				
	1/2	1/2	112.5 (250)	ALC50-B
9	3/4	1/2		ALC7550-B
	1	1/2		ALC1050-B
	3/4	3/4	112.5 (250)	ALC75-B
	1	3/4		ALC1075-B
ALC — Cushion Hanger — Furnish	ed with a 3/4" to 1/2"	reducer for 1/2" sten	ns	
	1/2	3/4 or 1/2		ALC50-12
	3/4	3/4 or 1/2	1.4 to 5.4 (3 to 12)	ALC7575-12
	1	3/4 or 1/2		ALC1075-12
600	1/2	3/4 or 1/2		ALC50-48
	3/4	3/4 or 1/2	5.4 to 21.6 (12 to 48)	ALC7575-48
	1	3/4 or 1/2		ALC1075-48
	1/2	3/4 or 1/2		ALC50-120
	3/4	3/4 or 1/2	21.6 to 54.0 (48 to 120)	ALC7575-120

3/4 or 1/2



ALC1075-120