




A-51™ Incandescent Factory Sealed Luminaires

For Group C and D Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS® for use with Threaded Metal Conduit.

NEC/CEC:

Class I, Division 1 and 2, Groups C, D
Class II, Division 1 and 2, Groups E, F, G
Class III

Type		Hub Size (Inches)	Catalog Number ②	
Pendant — One Hub, Rigid or Flexible Mounting				
	60-100 W (AAU-1N) A-21	1/2	AP1050	
		3/4	AP1075	
		1	AP10100	
	150-300 W (AAU-15N) A-23 PS-25	1/2	AP1550	
		3/4	AP1575	
		1	AP15100	
	200-300 W (AAU-2NS) PS-30	1/2	AP2050	
		3/4	AP2075	
		1	AP20100	
Ceiling — Four Hubs, Three Close-up Plugs				
	60-100 W (AAU-1N) A-21	1/2	AC1050	
		3/4	AC1075	
		1	AC10100	
	150-300 W (AAU-15N) A-23 PS-25	1/2	AC1550	
		3/4	AC1575	
		1	AC15100	
	200-300 W (AAU-2NS) PS-30	1/2	AC2050	
		3/4	AC2075	
		1	AC20100	
25° Stanchion — One Hub — Not UL Listed				
	60-100 W (AAU-1N) A-21	1-1/2 ②	AN10150	
		150-300 W (AAU-15N) A-23 PS-25	1-1/2 ②	AN15150
			200-300 W (AAU-2NS) PS-30	1-1/2 ②

① See A-51™ Incandescent Factory Sealed Luminaire Classified Area Suitability page for suitability of specific fixtures.

② 1-1/2" tapped hub furnished with a 1-1/2" to 1-1/4" reducer.