








# Code•Master™ Factory Sealed Strobe Luminaires

Explosionproof, Dust-Ignitionproof

**NEC:**  
 Class I, Division 1 and 2, Groups C, D  
 Class I, Division 2, Groups A, B  
 Class II, Division 1 and 2, Groups E, F, G  
 Class III  
 NEMA 3R, 4X

**NEC:**  
 Suitable for Wet Locations  
 Marine Outside Type (Saltwater)

## Strobes for the Hearing Impaired

	Type Mounting	Volts	Catalog Number — UL1971: Hearing-Impaired ①
<b>Pendant — One Hub 3/4" NPT, Rigid Conduit</b>			
		20-30 Vdc	CSSP752030DCCLP
<b>Ceiling — Four Hubs 3/4" NPT, Three Close-Up Plugs, Rigid Conduit</b>			
		20-30 Vdc	CSSC752030DCCLP
<b>Fixture Unit Only — Less Mounting Hood</b>			
		20-30 Vdc	CSSB752030DCCLP
<b>Fixture Unit Only — Less Mounting Hood</b>			
	4.7 kg (10.36 lb)	20-30 Vdc	CSST2030PDCCL
	Weight kg (lb)	Hub Size (Inches)	Catalog Number — UL1971: Hearing-Impaired
<b>Pendant Mounting Hood — One Hub 3/4" NPT, Rigid Conduit</b>			
	9.0 (19.84)	3/4	CAP-751971
<b>Ceiling Mounting Hood — Four Hubs 3/4" NPT, Three Close-Up Plugs, Rigid Conduit</b>			
	1.8 (3.97)	3/4	CAC-751971
<b>Bracket Mounting Hood — Four Hubs 3/4" NPT, Three Close-Up Plugs, Rigid Conduit</b>			
	2.7 (5.95)	3/4	CALB-751971

① Only clear globes are available for UL1971 applications.