

Code•Master™ 2 HID Factory Sealed Floodlights





Marine (Outside Type). Explosionproof

Integrally Ballasted. 150 W, 250 W, 400 W HPS; 150 W, 175 W, 250 W, 320 W, 350 W, 400 W PSMH. Mogul Base.

NEC:
Class 1, Division 1 and 2, Groups C, D
Marine Type Electric Fixtures
Outside Type (Salt Water)

Appleton

HID/FLOODLIGHT: NEC/CEC EXPLOSIONPROOF

	Lamp Watts	ANSI Lamp Type		Catalog Number ①③	
		HPS	PSMH	HPS	PSMH
Fixture Unit					
Furnished with Trunnion 3/4" hub. (3/4 – 14 NPT)					
	150	S55	M102	CFL150MT	CFP150MT
	175	—	M137/M152	—	CFP175MT
	250	S50	M138/M153	CFL250MT	CFP250MT
	320	—	M145	—	CFP320MT
	350	—	M131	—	CFP350MT
	400	S51	M135/M155	CFL400MT	CFP400MT
Fixture Unit with Junction Box for Horizontal or Vertical Mounting ②					
3/4" fixture hub and two conduit openings (3/4 – 14 NPT). 30" Flexible Coupling connects to 3/4" fixture hub and to 1/2" junction box opening. Furnished with one 3/4" Close-up Plug. Has Locking Screw for horizontal adjustment.					
	150	S55	M102	CFL150JBMT	CFP150JBMT
	175	—	M137/M152	—	CFP175JBMT
	250	S50	M138/M153	CFL250JBMT	CFP250JBMT
	320	—	M145	—	CFP320JBMT
	350	—	M131	—	CFP350JBMT
	400	S51	M135/M155	CFL400JBMT	CFP400JBMT
Fixture Unit with Pole-Top Mount (on 2" Threaded Pipe) ②					
2" tapered threads (2 – 11-1/2 NPT). Locking Screw for horizontal adjustment. 30" Flexible Coupling connects to 3/4" fixture hub (3/4 – 14 NPT) and to 1/2" pole-top opening (1/2-14 NPT).					
	150	S55	M102	CFL150SFMT	CFP150SFMT
	175	—	M137/M152	—	CFP175SFMT
	250	S50	M138/M153	CFL250SFMT	CFP250SFMT
	320	—	M145	—	CFP320SFMT
	350	—	M131	—	CFP350SFMT
	400	S51	M135/M155	CFL400SFMT	CFP400SFMT
Fixture Unit with Crossarm Mounting ②					
For mounting to flat surface. 180° horizontal adjustment with degree indicator. 30" Flexible Coupling connects to 3/4" fixture hub (3/4 – 14 NPT) and to any 1/2" opening (1/2 – 14 NPT).					
	150	S55	M102	CFL150CAMT	CFP150CAMT
	175	—	M137/M152	—	CFP175CAMT
	250	S50	M138/M153	CFL250CAMT	CFP250CAMT
	320	—	M145	—	CFP320CAMT
	350	—	M131	—	CFP350CAMT
	400	S51	M135/M155	CFL400CAMT	CFP400CAMT

① To order fixture with guard, add suffix **-G** before voltage suffix.

② Fixtures furnished with trunnion and bolts, flexible coupling and fittings, and mounting accessory. The trunnion provides vertical adjustment and the mounting accessory provides horizontal adjustment.

③ Change suffix **-MT** (120/208/240/277 V) to **-480** for 480 V.