

Code•Master™ PLT Factory Sealed Luminaires






Explosionproof, Dust-Ignitionproof

Integrally Ballasted. 26 W, 32 W, 42 W, 52 W, 64 W, 84 W Compact Fluorescent. For use with Threaded Metal Conduit.


NEC:
Class I, Division 1 and 2, Groups B♦, C, D
Class II, Division 1 and 2, Groups E, F, G
Class III
NEMA 4X
Suitable for use in wet locations

CEC:
Class I, Division 1 and 2, Groups B, C, D
Class II, Division 1 and 2, Groups E, F, G
Class III
CSA 4X

Mounting Hoods

	Hub Size (Inches)	Catalog Number
Pendant 	3/4	CAP-75
	1	CAP-100
Ceiling 	3/4	CAC-75
	1	CAC-100
Bracket 	3/4	CALB-75
	1	CALB-100
25° Stanchion 	1-1/4 or 1-1/2 ①	CAS-150 ①
Mounting Adapter with Connection Block 		CMAD-1

Fixture Units

	Line Voltage	Hz	Catalog Number
Ballast body with globe  26-42 W 52-84 W	120-277	50/60	CJB26FBU ②
	120-277	50/60	CJB32FBU ②
	120-277	50/60	CJB42FBU ②
	120-277	50/60	CMBF52BU
	120-277	50/60	CMBF64BU
	120-277	50/60	CMBF84BU

Electrical Specification

Lamp Wattage	Line Voltage	Frequency (Hz)	Line Amps	Input Watts	Min. Starting Temp
26 (1 x 26)	120-277	50/60	0.25-0.11	28	-18 °C (0 °F)
32 (1 x 32)	120-277	50/60	0.27-0.12	36	-18 °C (0 °F)
42 (1 x 42)	120-277	50/60	0.35-0.16	48	-18 °C (0 °F)
52 (2 x 26)	120-277	50/60	0.49-0.20	55	-30 °C (-22 °F)
64 (2 x 32)	120-277	50/60	0.57-0.24	67	-30 °C (-22 °F)
84 (2 x 42)	120-277	50/60	0.73-0.31	87	-30 °C (-22 °F)

♦ Fixtures are for use with Group B atmospheres only when used with Group B mounting hoods. For 26 W, 32 W, and 42 W fixtures only.

① 1-1/2" tapped hub furnished with 1-1/2" to 1-1/4" reducer.

② Denotes items that are suitable for Class I, Group B in addition to Class I, Groups C and D; and Class II, Groups E, F and G.

Shaded items are suitable for Class I, Group C in addition to Class I, Group D; Class II, Groups E, F and G; and Class III.

Appleton

FLUORESCENT/AREA: NEC/CEC EXPLOSIONPROOF