

Code•Master™ Jr. HID Factory Sealed Luminaires

Explosionproof, Dust-Ignitionproof

Integrally Ballasted. 50 W, 70 W, 100 W, 150 W HPS; 50 W, 70 W, 100 W, 175 W PSMH. 175 W MH. Medium Base. For Use with Threaded Metal Conduit.

NEC:
Class I, Division 1 and 2, Groups C, D
Class II, Division 1 and 2, Groups E, F, G
Class III
Marine type electric fixtures, outside type
(salt water)

CEC:
Class I, Division 1 and 2, Groups B♦, C, D
Class II, Division 1 and 2, Groups E, F, G
Class III
Type 4X
Exd IIB + H₂

HID/AREA: NEC/CEC EXPLOSIONPROOF



Lamp Watts	ANSI Lamp Type ⑥		Hub Size ⑦ (Inches)	Catalog Number ②		
	HPS	PSMH/MH		HPS ①	PSMH	MH ⑧
Pendant — One Hub, Rigid or Flexible Mounting						
50	S68	M110	3/4	CJLP5075MT ③	CJHP5075MT ③	—
				CJLP5075TTCN ⑨ ③	CJHP5075TTCN ⑨ ③	—
			1	CJLP5010MT ③	CJHP5010MT ③	—
				CJLP5010TTCN ⑨ ③	CJHP5010TTCN ⑨ ③	—
70	S62	M98	3/4	CJLP7075MT ④	CJHP7075MT ④	—
				CJLP7075TTCN ⑨ ⑤	CJHP7075TTCN ⑨ ⑤	—
			1	CJLP7010MT ④	CJHP7010MT ④	—
				CJLP7010TTCN ⑨ ⑤	CJHP7010TTCN ⑨ ⑤	—
100	S54	M90	3/4	CJLP1075MT ④	CJHP1075MT ④	—
				CJLP1075TTCN ⑨ ⑤	CJHP1075TTCN ⑨ ⑤	—
			1	CJLP1010MT ④	CJHP1010MT ④	—
				CJLP1010TTCN ⑨ ④	CJHP1010TTCN ⑨ ⑤	—
150	S55	—	3/4	CJLP1575MT ④	—	—
				CJLP1575TTCN ⑨ ⑤	—	—
			1	CJLP1510MT ④	—	—
				CJLP1510TTCN ⑨ ④	—	—
175	—	M152	3/4	—	CJPP1775MT ④	CJHP1775MTCN ⑨ ④
				—	CJPP1775TTCN ⑨ ⑤	CJHP1775TTCN ⑨ ⑤
			1	—	CJPP1710MT ④	CJHP1710MTCN ⑨ ④
				—	CJPP1710TTCN ⑨ ⑤	CJHP1710TTCN ⑨ ⑤

Appleton®



Ceiling — Four Hubs, Three Close-Up Plugs						
50	S68	M110	3/4	CJLC5075MT ③	CJHC5075MT ③	—
				CJLC5075TTCN ⑨ ③	CJHC5075TTCN ⑨ ③	—
			1	CJLC5010MT ③	CJHC5010MT ③	—
				CJLC5010TTCN ⑨ ③	CJHC5010TTCN ⑨ ③	—
70	S62	M98	3/4	CJLC7075MT ④	CJHC7075MT ④	—
				CJLC7075TTCN ⑨ ⑤	CJHC7075TTCN ⑨ ⑤	—
			1	CJLC7010MT ④	CJHC7010MT ④	—
				CJLC7010TTCN ⑨ ⑤	CJHC7010TTCN ⑨ ⑤	—
100	S54	M90	3/4	CJLC1075MT ④	CJHC1075MT ④	—
				CJLC1075TTCN ⑨ ⑤	CJHC1075TTCN ⑨ ⑤	—
			1	CJLC1010MT ④	CJHC1010MT ④	—
				CJLC1010TTCN ⑨ ⑤	CJHC1010TTCN ⑨ ⑤	—
150	S55	—	3/4	CJLC1575MT ④	—	—
				CJLC1575TTCN ⑨ ⑤	—	—
			1	CJLC1510MT ④	—	—
				CJLC1510TTCN ⑨ ⑤	—	—
175	—	M152	3/4	—	CJPC1775MT ④	CJHC1775MTCN ⑨ ④
				—	CJPC1775TTCN ⑨ ⑤	CJHC1775TTCN ⑨ ⑤
			1	—	CJPC1710MT ④	CJHC1710MTCN ⑨ ④
				—	CJPC1710TTCN ⑨ ⑤	CJHC1710TTCN ⑨ ⑤

- ① Add suffix **-R** for "Hot Restrike" and **-S** for "Smart Starter" options.
- ② To order fixture with guard, add suffix **-G** before adding voltage suffix.
- ③ For 480 V, contact your sales representative.
- ④ Change voltage suffix **-MT** to **-48** for 480 V.
- ⑤ Change voltage suffix **-TT** (120/277/347 V) to **-MT** for 120/208/240/277 V, **-C2** for 208 V, **-C3** for 240 V, **-C6** for 480 V, or **-C7** for 600 V. These voltage suffixes have CSA Certification only.
- ⑥ Refer to lamp manufacturer's data regarding lamp burning position restrictions.
- ⑦ Fixtures with 1" hubs listed for Class I, Group D, and Class II, Groups E, F, G only.
- ⑧ Mercury vapor and metal halide luminaires are not available for purchase within the United States. Please check with your countries governing legislation regarding allowable lamp types before ordering.
- ⑨ Catalog numbers with **-CN** suffix have CSA Certification only.

♦ Shaded area indicates items suitable for Class I, Division 1, Group B.