

Flexible Fixture Hangers, EXJF Couplings, ESD and ESS Swivels

Explosionproof, Dust-Ignitionproof

UNILETS® for use with Threaded Metal Conduit. For Use with Rigid Fixture Hangers Where Fixture Stem is More Than 304.8 mm (12") Long.

NEC/CEC:

Class I, Division 1 and 2, Groups A, B♦, C, D

Class II, Division 1 and 2, Groups E, F, G

Class III

POLES/HANGERS: NEC/CEC EXPLOSIONPROOF FLEXIBLE FIXTURE HANGERS

	Size (Inches)	Millimeters (Inches)		Catalog Number
		Flexible Length	Overall Length	

EXJF Flexible Fixture Hanger ①



Raintight construction. Supplied with two female hubs, each with a removable close nipple. Can be used to make male to male, female to male or female to female. Setscrew with screwdriver slot allows locking of conduit—prevents fixture stem from turning. Maximum load 120 pounds.

1/2	102 (4.00)	276 (10.88)	EXJF14
3/4	102 (4.00)	278 (10.94)	EXJF24
1/2	152 (6.00)	327 (12.88)	EXJF16
3/4	152 (6.00)	329 (12.94)	EXJF26
1/2	203 (8.00)	329 (14.88)	EXJF18
3/4	203 (8.00)	379 (14.94)	EXJF28
1/2	254 (10.00)	429 (16.88)	EXJF110
3/4	254 (10.00)	430 (16.94)	EXJF210
1/2	305 (12.00)	480 (18.88)	EXJF112
3/4	305 (12.00)	481 (18.94)	EXJF212
1/2	381 (15.00)	556 (21.88)	EXJF115
3/4	381 (15.00)	557 (21.94)	EXJF215
1/2	457 (18.00)	632 (24.88)	EXJF118
3/4	457 (18.00)	633 (24.94)	EXJF218

Swivel Hangers — Setscrew with screwdriver slot allows locking of conduit — Prevents fixture stem from turning



ESD Swivel

15° swivel from center and full 360° free swing.

1/2	ESD50 ②
3/4	ESD75 ②



ESS Swivel

15° swivel from center.

1/2	ESS50 ②
3/4	ESS75 ②

① Available in stainless steel. Add suffix **-SS** to catalog number. Consult your local sales representative.

② Not CSA Certified.

♦ Shaded area indicates items suitable for Class I, Groups A and B in addition to Class I, Groups C and D; Class II, Groups E, F and G; and Class III.