


ATX™ FD Series Cylindrical Fluorescent Luminaires

Standard and Emergency Battery Back-Up. Flameproof

ATEX/IECEX:
 Zone 1 and 2 - 21 and 22
 II 2 GD
 IP66/68

Ordering Information – Standard Versions – Continued

Two M20 threaded entries, supplied with one M20 aluminum blanking plug.
 Connection via 1 x 3 double deck terminals.
 Capacity (flexible/solid): 0.75 mm² to 2.5 mm² (0.001 in² to 0.004 in²).



For Bi-pin (G13) Fluorescent Lamps - T8, 26 mm (1.02 in) or T12, 38 mm (1.50 in)
 110 to 254 Vac/Vdc, 50/60 Hz – Electronic Ballast
 Power factor > 0.95

Wattage (W)	No. of Lamps	Gas Group	Model	Weight kg (lb)	Volume dm ³ (in ³)	Catalog Number
18	2	IIC	0.6	9.7 (21.38)	58 (3539.38)	FDB218BUM
36	2	IIB	1.2	15.3 (33.73)	99 (6041.35)	FDB236BUM
	3	IIB	1.2	16.3 (35.94)	99 (6041.35)	FDB336BUM
	1	IIB	1.5	17.0 (37.48)	119 (7261.83)	FDB158BUM
58	2	IIB	1.5	18.2 (40.12)	119 (7261.83)	FDB258BUM
	3	IIB	1.5	19.2 (42.33)	119 (7261.83)	FDB358BUM


For 2G11 Compact Fluorescent Lamps – TC-L
 230 V - 50 Hz – Magnetic Ballast – Starter Ignition
 Compensated power supply – power factor > 0.9 – Lamps supplied

18	1	IIC	0.3	9.0 (19.8)	58 (3539.38)	FDC118XCM
	2	IIC	0.3	9.7 (21.38)	58 (3539.38)	FDC218XCM
36	1	IIB+H ₂	0.6	14.7 (32.41)	99 (6041.35)	FDC136XCM
	2	IIB+H ₂	0.6	15.3 (33.73)	99 (6041.35)	FDC236XCM

Emergency Versions

Two M20 threaded entries, supplied with one M20 aluminum blanking plug.
 Connection via 1 x 4 double deck terminals.
 Capacity (flexible/solid): 0.75 mm² to 2.5 mm² (0.001 in² to 0.004 in²).

For Bi-pin (G13) Fluorescent Lamps – T8, 26 mm (1.02 in) or T12, 38 mm (1.50 in)
 110 to 254 Vac/Vdc, 50/60 Hz – Electronic Ballast
 3 hour duration - battery pack 6 V 4 Ah - Power factor > 0.95 -
 Self test every month.



Wattage (W)	No. of Lamps	Gas Group	Model	Line Output	Weight kg (lb)	Volume dm ³ (in ³)	Catalog Number
18	2	IIC	0.6	29%	11.6 (25.57)	58 (3539.38)	FDB218BUME
36	2	IIB	1.2	16%	17.2 (37.92)	99 (6041.35)	FDB236BUME
58	2	IIB	1.5	11%	20.2 (44.53)	119 (7261.83)	FDB258BUME