Mercmaster™ III HID 50-250 Watt PRE-PAK™ Luminaires

Factory-Assembled Fixtures

For 70 W, 100 W or 150 W High Pressure Sodium Lamps, or 100 W or 175 W Pulse Start Metal Halide Lamps. Mogul Base Lamps.

NEC/CEC: VEC/CEC: Class I, Division 2, Groups A, B, C, D Class I, Zone 2, AEx nA nR IIC (Z2) Class I, Zone 2, Ex nR IIC (Z) Class I, Zone 2, AEx nR IIC (ZB) NEC/CEC: Class II, Division 1 and 2, Groups E, F, G Class III Simultaneous Exposure (Class I, Division 2/ Class II, Division 1)

NEC/CEC: Fixtures Outside Type (Salt Water) Type 4X IP66

These pre-packaged fixture component combinations are delivered fully assembled and packed in a single carton. They are available with or without lamp, and with choice of globe or NEMA Type I, III or V refractors - all with or without guards. PRE-PAK units simplify ordering, stocking and shipping, and result in savings on job-site assembly and installation time and costs.

Catalog numbers do not include mounting hood or reflector. For mounting hood and reflectors selection, see below and order separately. Hood and Reflector will be packaged separately.











PRE-PAK Fixtures ①

Lamp Type and Watts	Ballast Assembly with Globe Only	Ballast Assembly with Globe and Guard	Ballast Assembly with G3 Globe Only	Ballast Assembly with Refractor Only ③	Ballast Assembly with Refractor and Guard
100 W PSMH ②	KPBU100H-MT	KPBU100HG-MT	_	KPBU100HJ5-MT	KPBU100HJ5G-MT
175 W PSMH	KPBU175P-MT	KPBU175PG-MT	_	KPBU175PJ5-MT	KPBU175PJ5G-MT
70 W HPS	KPBU70L-MT	KPBU70LG-MT	_	KPBU70LJ5-MT	KPBU70LJ5G-MT
100 W HPS	KPBU100L-MT	KPBU100LG-MT	KPBUG3100L-MT	KPBU100LJ5-MT	KPBU100LJ5G-MT
150 W HPS	KPBU150L-MT	KPBU150LG-MT	<u> </u>	KPBU150LJ5-MT	KPBU150LJ5G-MT

Mounting Hoods

mounting riods					
Description		Hub Size (Inches)	Catalog Number		
Pendant	6	3/4	KPA-75		
One Hub, Rigid Mounting	***	1	KPA-100		
Pendant — Flexible		3/4	KPAF-75		
One Hub, Flexible Mounting		1	KPAF-100		
Pendant Cone		3/4	KPCH-75		
One Hub, Rigid		1	KPCH-100		
Ceiling	. 6.	3/4	KPC-75		
Five Hubs, Four Close-Up Plugs		1	KPC-100		
Wall		3/4	KPWB-75		
Five Hubs, Four Close-Up Plugs		1	KPWB-100		
25° Stanchion		1-1/4	KPS-125		
One Hub		1-1/2	KPS-150		
90° Stanchion	5	1-1/4	KPST-125		
One Hub		1-1/2	KPST-150		

Description	Catalog Number
Standard Dome For Globe Fixtures	KR2-ST
30° Angle For Globe Fixtures	KR2-AN
Standard Dome For Glass Refractor Fixtures	CMR-4ST
30° Angle For Glass Refractor Fixtures	CMR-4AN

³ Refractor catalog numbers listed are for NEMA Type V. To order fixture with Type III refractor, change J5 in catalog number to J3; for Type I refractor, change J5 to J1.



① All catalog numbers above are fixtures without lamp. To order fixture complete with appropriate installed lamp, add suffix L to catalog number. All PRE-PAK fixtures include multi-tap ballast for operation on 120 V, 208 V, 240 V or 277 V lines. Fixture component combinations listed are furnished completely assembled in a single carton.

② 100 W fixtures use ED-28 mogul base lamps.