

ATX™ RE Series Recessed and Surface Mounting Fluorescent Luminaires

Standard and Emergency Back-Up. Increased Safety

ATEX/IECEX:
 Zone 1 and 2 - 21 and 22
 II 2 GD
 IP66 - IK09/10

FLUORESCENT/AREA: ATEX/IECEX STANDARD AND EMERGENCY BACK-UP

Recessed — 110/254 Vac/Vdc, 50/60 Hz — Front Access — White Painted Steel Housing

| Version | Reflector | Wiring | Weight kg (lb) | Volume dm ³ (in ³) | Catalog Number ①②③④⑤⑥⑦ |
|---|---------------------|---------|-------------------|--|---------------------------|
| Standard Version — Bi-pin Lamps (G13) | | | | | |
| 2 x 18 W | Polycarbonate | Loop | 14 (30.86) | 64 (3905.52) | REB218BUFL |
| | | Through | 14 (30.86) | 64 (3905.52) | REB218BUFT |
| 4 x 18 W | White Painted Steel | Loop | 21 (46.30) | 93 (5675.21) | REB418BUFLP |
| | | Through | 21 (46.30) | 93 (5675.21) | REB418BUFTP |
| 2 x 36 W | Polycarbonate | Loop | 19 (41.89) | 108 (6590.56) | REB236BUFL |
| | | Through | 19 (41.89) | 108 (6590.56) | REB236BUFT |
| 4 x 36 W | White Painted Steel | Loop | 29 (63.93) | 158 (9641.75) | REB436BUFLP |
| | | Through | 29 (63.93) | 158 (9641.75) | REB436BUFTP |
| 2 x 58 W | Polycarbonate | Loop | 22 (48.50) | 130 (7933.09) | REB258BUFL |
| | | Through | 22 (48.50) | 130 (7933.09) | REB258BUFT |
| 4 x 58 W | White Painted Steel | Loop | 32 (70.55) | 190 (11594.51) | REB458BUFLP |
| | | Through | 32 (70.55) | 190 (11594.51) | REB458BUFTP |
| 3 Hours Emergency Version — Bi-pin Lamps (G13) | | | | | |
| 2 x 18 W | Polycarbonate | Loop | 14 (30.86) | 64 (3905.52) | REB218BUFLEP |
| | | Through | 14 (30.86) | 64 (3905.52) | REB218BUFTPEP |
| 4 x 18 W | White Painted Steel | Loop | 21 (46.30) | 93 (5675.21) | REB418BUFLEP |
| | | Through | 21 (46.30) | 93 (5675.21) | REB418BUFTPEP |
| 2 x 36 W | Polycarbonate | Loop | 19 (41.89) | 108 (6590.56) | REB236BUFLE |
| | | Through | 19 (41.89) | 108 (6590.56) | REB236BUFTE |
| 4 x 36 W | White Painted Steel | Loop | 29 (63.93) | 158 (9641.75) | REB436BUFLEP |
| | | Through | 29 (63.93) | 158 (9641.75) | REB436BUFTPEP |
| 2 x 58 W | Polycarbonate | Loop | 22 (48.50) | 130 (7933.09) | REB258BUFLE |
| | | Through | 22 (48.50) | 130 (7933.09) | REB258BUFTE |
| 4 x 58 W | White Painted Steel | Loop | 32 (70.55) | 190 (11594.51) | REB458BUFLEP |
| | | Through | 32 (70.55) | 190 (11594.51) | REB458BUFTPEP |

- ① For surface mounting lighting, replace letter **F** with letter **M** in the 9th position; example: REB218BUML.
- ② For 3 hours emergency version - Battery 6 V - 4 Ah, add suffix **E** to the end of the catalog number; example: REB218BUFLE.
- ③ For 1 hour 30 emergency (combined) - Battery 6 V - 7 Ah, add suffix **E1** to the end of the catalog number; example: REB218BUFLE1.
- ④ For 3H Emergency (combined) - Battery 6 V - 7 Ah, add suffix **E7** to the end of the catalog number; example: REB218BUFLE7.
- ⑤ For fixture without a safety switch, add suffix **N** to the end of the catalog number; example: REB218BUFLN.
- ⑥ For fixture with a white painted steel internal reflector, add suffix **P** to the end of the catalog number; example: REB218BUFLP.
- ⑦ For fixture with 316L stainless steel housing and integral frame and natural finish, add suffix **S** to the end of the catalog number; example: REB218BUFLS.