










# V-51™ Incandescent Luminaires

## Enclosed and Gasketed

UNILETS® for use with threaded metal conduit.

**NEC:**  
Class I, Division 2, Groups A, B, C, D

**CEC:**  
Class I, Division 2, Groups A, B, C, D  
Class II, Divisions 1 and 2, Groups E, F, G ②  
Class III  
Enclosure 3R

Description	Hub Size (Inches)	Catalog Numbers Malleable Iron
<b>Pendant and Ceiling Mounting Hoods — Furnished with connection block, gasket and screws</b>		
<b>Pendant Mounting</b>		
	1/2	VA50
	3/4	VA75
	1	VA100
	1-1/4	VA125
<b>Dead-End — Ceiling Mounting</b>		
	1/2	V50
	3/4	V75
<b>Feed-Thru — Ceiling Mounting</b>		
	1/2	VC50
	3/4	VC75
<b>Three Hubs — Ceiling Mounting</b>		
	1/2	VT50
	3/4	VT75
<b>Four Hubs — Ceiling Mounting</b>		
	1/2	VX50
	3/4	VX75
<b>Five Hubs — Ceiling Mounting ③</b>		
	1/2	VXHA50
	3/4	VXHA75
	1	VXHA100
<b>Wall and Stanchion Mounting Hoods — Furnished with connection block, gasket and screws</b>		
<b>One Opening — Wall Mounting ④ — 1 tapped hole in center of flange</b>		
	1/2	VGA50
	3/4	VGA75
<b>Feed-Thru — Wall Mounting ④ — 2 tapped vertical feed-thru hubs</b>		
	1/2	VD50
	3/4	VD75
<b>Three Hubs and One Opening — Wall Mounting ④ — 3 hubs plus 1 tapped opening in center of flange</b>		
	1/2	VGAT50
	3/4	VGAT75

② 300 W PS-25 not approved for Class II, Division 1 and 2, Group G; Class III.

③ Four close-up plugs furnished.

④ Mounting hoods for wall installations can only be used with 30° angle reflectors.