

SPECIFICATIONS

I-Purge® Standard Inflatable Systems (Sold as a Complete System)

| ITEM NO. | DIMENSIONS | | STANDARD HARNESS LENGTH | | DESCRIPTION |
|----------|------------|---------|-------------------------|---------|--|
| | ENGLISH | METRIC | ENGLISH | METRIC | |
| ABLD 2* | 2" | 51 mm | 11" | 279 mm | 2" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 3* | 3" | 76 mm | 11" | 279 mm | 3" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 4 | 4" | 102 mm | 11" | 279 mm | 4" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 5 | 5" | 127 mm | 11" | 279 mm | 5" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 6 | 6" | 152 mm | 11" | 279 mm | 6" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 8 | 8" | 203 mm | 11" | 279 mm | 8" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 10 | 10" | 254 mm | 12" | 305 mm | 10" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 12 | 12" | 305 mm | 12" | 305 mm | 12" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 14 | 14" | 356 mm | 16" | 406 mm | 14" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 16 | 16" | 406 mm | 16" | 406 mm | 16" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 18 | 18" | 457 mm | 16" | 406 mm | 18" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 20 | 20" | 508 mm | 18" | 457 mm | 20" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 22 | 22" | 559 mm | 18" | 457 mm | 22" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 24 | 24" | 610 mm | 18" | 457 mm | 24" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 26 | 26" | 660 mm | 20" | 509 mm | 26" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 28 | 28" | 711 mm | 20" | 509 mm | 28" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 30 | 30" | 762 mm | 20" | 509 mm | 30" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 32 | 32" | 813 mm | 20" | 509 mm | 32" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 34 | 34" | 864 mm | 20" | 509 mm | 34" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 36 | 36" | 914 mm | 20" | 509 mm | 36" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 38 | 38" | 965 mm | 36" | 914 mm | 38" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 40 | 40" | 1016 mm | 36" | 914 mm | 40" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 42 | 42" | 1066 mm | 36" | 914 mm | 42" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 44 | 44" | 1117 mm | 36" | 914 mm | 44" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 46 | 46" | 1168 mm | 42" | 1067 mm | 46" I-Purge Double Purge Bag System with High Heat Harness |
| ABLD 48 | 48" | 1219 mm | 42" | 1067 mm | 48" I-Purge Double Purge Bag System with High Heat Harness |

Modular Components (ABLD-Size-MOD A and ABLD-Size-MOD B) Sold Separately


I-Purge Isolator®

| ITEM NO. | DIMENSIONS | | DESCRIPTION |
|----------|------------|---------|---|
| | ENGLISH | METRIC | |
| ISO 2 | 2" | 51 mm | 2" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 3 | 3" | 76 mm | 3" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 4 | 4" | 102 mm | 4" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 5 | 5" | 127 mm | 5" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 6 | 6" | 152 mm | 6" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 8 | 8" | 203 mm | 8" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 10 | 10" | 254 mm | 10" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 12 | 12" | 305 mm | 12" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 14 | 14" | 356 mm | 14" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 16 | 16" | 406 mm | 16" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 18 | 18" | 457 mm | 18" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 20 | 20" | 508 mm | 20" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 22 | 22" | 559 mm | 22" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 24 | 24" | 610 mm | 24" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 26 | 26" | 660 mm | 26" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 28 | 28" | 711 mm | 28" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 30 | 30" | 762 mm | 30" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 32 | 32" | 813 mm | 32" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 34 | 34" | 863 mm | 34" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 36 | 36" | 914 mm | 36" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 38 | 38" | 965 mm | 38" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 40 | 40" | 1016 mm | 40" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 42 | 42" | 1066 mm | 42" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 44 | 44" | 1117 mm | 44" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 46 | 46" | 1168 mm | 46" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |
| ISO 48 | 48" | 1219 mm | 48" I-Purge Isolator One-Sided Plug with 10' Hose and Valve |

Accessory Components Optional Harness Lengths

| ITEM NO. | DIMENSIONS | | DESCRIPTION |
|-----------------|------------|----------|--|
| | ENGLISH | METRIC | |
| ABLD-ELH-24 | 24" | 610 mm | 24" (2') Extended Length High Heat Harness |
| ABLD-ELH-36 | 36" | 914 mm | 36" (3') Extended Length High Heat Harness |
| ABLD-ELH-48 | 48" | 1219 mm | 48" (4') Extended Length High Heat Harness |
| ABLD-ELH-72 | 72" | 1828 mm | 72" (6') Extended Length High Heat Harness |
| ABLD-ELH-CUSTOM | Any Size | Any Size | Custom Lengths Available Upon Request |
| ABLD-CNADP | NA | NA | 1/4" Female MPT to 1/4" Female BSPP Conversion |

For additional product information, quotations and ordering, please contact:



Aquasol Corporation

80 Thompson Street
N. Tonawanda, NY 14120 USA

Toll Free: 1.800.564.WELD (9353)
Phone: 716.564.8888
Fax: 716.564.8889

Email: info@aquasolcorporation.com
aquasolwelding.com

Distributed By:



I-Purge®

MODULAR INFLATABLE BLADDER SYSTEM

US & FOREIGN PATENTS PENDING
CE APPROVED

THE MOST VERSATILE & ADAPTABLE SOLUTION FOR PIPE PURGING



EXTENDED HARNESS

To Accommodate Heat Zones

I-PURGE® REDUCER

For Unique Pipe Combinations

I-PURGE ISOLATOR®

One Sided Purge Plug