



The All Purpose Solution

- For Conventional Uses in the Field such as Heating, Air Conditioning, Refrigeration and Acting as a Vapor Barrier
- Capping Pipe Ends During Transport
- Controls Release of Gas by Sealing Root Gap

High Heat Temperature Resistant

- Aluminum Coated Adhesive Withstands Temperatures up to 500°F (260°C)





High Quality & Safe Components

- Halogen and Chlorofluorocarbon Free

**PROMOTES
SAFETY
IN THE
WORKPLACE**

SPECIFICATIONS FOR ALUMINUM WELDING TAPE


EZ Tape® Types and Sizes

PRODUCT	ITEM NO.	DESCRIPTION	WIDTH		ADHESIVE FREE "ZONE" WIDTH		LENGTH	
			ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC
	EZ-ZT 2.5	EZ Zone® Tape	2.5"	64 mm	1"	25 mm	75'	23 m
	EZ-ZT 4.0	EZ Zone® Tape	4.0"	102 mm	2"	51 mm	75'	23 m
	EZ-T 1.0	EZ Tape® Fully-coated	1.0"	25 mm	N/A		75'	23 m
	EZ-T 2.0	EZ Tape® Fully-coated	2.0"	51 mm	N/A		75'	23 m

▶ Heat Resistance:	Adhesive	500°F	260°C
	Aluminum Foil	1100°F	593°C
▶ Minimum Application Temperature		10°F	-12.5°C

For additional product information, quotations and ordering, please contact:

Distributed By:



Aquasol Corporation

80 Thompson Street
N. Tonawanda, NY 14120 USA

Toll Free: 1.800.564.WELD (9353)
Phone: 716.564.8888
Fax: 716.564.8889

Email: info@aquasolcorporation.com
aquasolwelding.com

