

Spacer Characteristics

- Provides Required 1/8" Minimum Gap for Plate/Pipe Projects As Required by AWS Code D1.6/D1.6M Stainless Steel Structural Code
- Highly Incompressible
- 100% Biodegradable & Environmentally Friendly
- Leaves Behind No Harmful Trace Elements

Spacer Installation & Removal

- Insert SoluShim® Sticks Between Plates to Create Required Spacing
- SoluShim® Sticks Can Be Bent to Form a 90° Angle (Secure with Aquasol® Water Soluble Tape if Necessary)
- Tack Weld the Joint As Normal Securing Even Gap
- Introduce Water to Dissolve and Easily Remove

**ELIMINATE GUESSWORK IN PIPE FIT UP,
ALLOWING FOR A PRECISE AND GUARANTEED MINIMUM GAP, EVERY TIME!**

SPECIFICATIONS

SoluShim® Types and Sizes

ITEM NO.	THICKNESS		SIZE		PACKAGING	CASE PACK
	ENGLISH	METRIC	ENGLISH	METRIC		
SS-2-38-132	1/32"	0.8 mm	3/8" x 2"	9 mm x 50.5 mm	100 pieces/polybag	10 polybags per case (1000 pieces)
SS-2-38-16	1/16"	1.6 mm	3/8" x 2"	9 mm x 50.5 mm	100 pieces/polybag	10 polybags per case (1000 pieces)
SS-2-38-332	3/32"	2.0 mm	3/8" x 2"	9 mm x 50.5 mm	100 pieces/polybag	10 polybags per case (1000 pieces)
SS-2-38-18	1/8"	3.3 mm	3/8" x 2"	9 mm x 50.5 mm	100 pieces/polybag	10 polybags per case (1000 pieces)
SS-4-38-132	1/32"	0.8 mm	3/8" x 4"	9 mm x 101 mm	50 pieces/polybag	20 polybags per case (1000 pieces)
SS-4-38-16	1/16"	1.6 mm	3/8" x 4"	9 mm x 101 mm	50 pieces/polybag	20 polybags per case (1000 pieces)
SS-4-38-332	3/32"	2.0 mm	3/8" x 4"	9 mm x 101 mm	50 pieces/polybag	20 polybags per case (1000 pieces)
SS-4-38-18	1/8"	3.3 mm	3/8" x 4"	9 mm x 101 mm	50 pieces/polybag	20 polybags per case (1000 pieces)

*Custom thicknesses and sizes available upon request.

For additional product information,
quotations and ordering, please contact:

Distributed By:



Aquasol Corporation

80 Thompson Street
N. Tonawanda, NY 14120 USA

Toll Free: 1.800.564.WELD (9353)
Phone: 716.564.8888
Fax: 716.564.8889

Email: info@aquasolcorporation.com
aquasolwelding.com