

Low Profile IN-AND-OUT™ Covers for New or Existing Construction

Low profile when not in use and a deeper, extra duty weatherproof in use cover when cord is plugged in. Non-metallic cover and base. Comes in clear or textured/ paintable white. UV rated plastic for long outdoor life.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	ORIENTATION/COVER COLOR	UNIT PKG	STD PKG	DIM A	DIM B	DIM C IN	DIM C OUT	DIM D	DIM E
60VC	00682	Vertical/Clear	1	4	6.274	3.752	1.670	3.005	--	--
60VW	00680	Vertical/White	1	4	6.274	3.752	1.670	3.005	--	--
61VC	00683	Vertical/Clear	1	4	6.274	3.752	1.670	3.005	5.561	4.250
61VW	00681	Vertical/White	1	4	6.274	3.752	1.670	3.005	5.561	4.250
60HC	00686	Horizontal/Clear	1	4	4.192	5.836	1.670	3.005	--	--
60HW	00684	Horizontal/white	1	4	4.192	5.836	1.670	3.005	--	--
61HC	00687	Horizontal/Clear	1	4	4.192	5.836	1.670	3.005	3.500	5.561
61HW	00685	Horizontal/white	1	4	4.192	5.836	1.670	3.005	3.500	5.561

UL **SP** **PATENTED.**
E170558 LR49636 **MADE IN USA.**

Note: Meets 2021 NEC section 406.9 (B) for the protection of exterior outlets where an extra duty weatherproof in use cover is required for 15 or 20 AMP receptacles installed outdoors.

ADDITIONAL PATENTS PENDING.

FEATURES AND BENEFITS

- Low profile when not in use
- IN position provides a sealed box to keep bugs out
- Extends quickly and easily into the OUT position to accommodate a plug
- Fits over all boxes or openings in new or existing projects
- Installed gaskets
- Extra duty
- The 61 Series has an installed, oversized base for large openings or a 3.5" round outlet box
- Install option: Cover is removable for easier device installation
- Vertical and horizontal styles
- Weatherproof in use

INSTALLATION INSTRUCTIONS



1 Feed device through opening (cover is removable for easier access).

2 Install wiring device per manufacturer's instructions, Local and National Electrical Codes using the pre-drilled holes in base.

3 Install plate and the installation is done!




60VW
IN for GOOD LOOKS and to stay bug free




61HW
OUT to PLUG IN for weatherproof in use!




To close: Bow out sides of extended cover and push in.



60VC



60V



61V

61 Series base shown separately for dimensional purposes only.

Scan For Video



IN-AND-OUT™ COVER INCLUDES

Low profile cover, (1) standard duplex and (1) standard GFCI face plate, installation screws, and installed gaskets.



Bug Plugs ship installed in all IN BOX styles to seal unused cord hole openings.