

**Super-E, three phase, TEFC, foot mounted, with internal Baldor-Reliance® Shaft Grounding Brush**

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>Foot mounted (continued)</b>											
15	3600	254T	<b>EM2394T-BG</b>	4,583	HV3	23.30	253	91	230/460	17.5	8,30
	1800	254T	<b>EM2333T-BG</b>	4,230	HV3	23.30	274	92.4	230/460	18.1	8,30
	1200	284T	<b>EM4100T-BG</b>	6,881	HV3	27.76	372	91.7	230/460	21	8,30
20	1800	256T	<b>EM2334T-BG</b>	5,037	HV3	23.30	290	93	230/460	24	8,30
	1200	286T	<b>EM4102T-BG</b>	8,999	HV3	27.76	406	91.7	230/460	27	8,30
25	1800	284T	<b>EM4103T-BG</b>	6,514	HV3	27.76	420	93.6	230/460	30	8,30
	1200	324T	<b>EM4111T-BG</b>	10,227	HV3	30.39	475	93	230/460	32	8,30
30	1800	286T	<b>EM4104T-BG</b>	7,636	HV3	27.76	437	93.6	230/460	38	8,30
40	1800	324T	<b>EM4110T-BG</b>	9,944	HV3	30.28	578	94.1	230/460	48	8,30
50	1800	326T	<b>EM4115T-BG</b>	10,810	HV3	30.28	641	94.5	230/460	58	8,30
<b>C-Face, foot mounted</b>											
1/2	1800	56C	<b>CEM3538-BG</b>	1,406	HV3	12.23	33	82.5	208-230/460	0.8	8
3/4	1800	56C	<b>CEM3542-BG</b>	1,451	HV3	12.23	37	84	208-230/460	1.1	8,12
1	1800	143TC	<b>CEM3546T-BG</b>	1,494	HV3	13.29	38	85.5	230/460	1.5	8,30
1 1/2	1800	145TC	<b>CEM3554T-BG</b>	1,540	HV3	13.29	41	86.5	230/460	2.2	8,30
2	1800	145TC	<b>CEM3558T-BG</b>	1,584	HV3	13.29	45	86.5	230/460	2.9	8,30
3	1800	182TC	<b>CEM3611T-BG</b>	1,826	HV3	16.55	70	89.5	230/460	4.2	8,30
5	1800	184TC	<b>CEM3615T-BG</b>	1,956	HV3	18.05	93	89.5	230/460	6.7	8,30

(a) See notes on inside back flap.

■ Cast iron frame

\*IP54 when drain fitting kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)

Information

General purpose  
Single phase

General purpose  
Three phase

Severe duty

Large Motors  
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty