

General purpose, three phase, totally enclosed, C-Face, foot mounted

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
575 volts (continued)												
5	3600	184TC	TEFC	CEM3613T-5	1,729	GE3	16.55	78	88.5	575	4.7	1
		184TC	TEFC	CEM3663T-5	2,384	GE3	16.00	99	88.5	575	4.7	1
	1800	184TC	TEFC	CEM3615T-5	1,449	GE3	18.05	93	89.5	575	5.3	1
		184TC	TEFC	CEM3665T-5	2,062	GE3	16.00	113	89.5	575	5.3	1
7 1/2	3600	213TC	TEFC	CEM3769T-5	2,893	GE3	19.20	179	89.5	575	7.4	1
	1800	213TC	TEFC	CEM3710T-5	2,142	GE3	19.76	129	91.7	575	7.6	1
		213TC	TEFC	CEM3770T-5	2,799	GE3	19.20	170	91.7	575	7.5	1
10	3600	215TC	TEFC	CEM3711T-5	2,674	GE3	18.63	123	90.2	575	9.5	1
		215TC	TEFC	CEM3771T-5	3,336	GE3	19.20	182	90.2	575	9.3	1
	1800	215TC	TEFC	CEM3714T-5	2,391	GE3	21.26	165	91.7	575	9.6	1
		215TC	TEFC	CEM3774T-5	3,101	GE3	19.20	231	91.7	575	9.8	1
15	3600	215TC	TEFC	CEM3713T-5	3,679	GE3	21.26	169	91	575	13.6	1
	1800	254TC	TEFC	CEM2333T-5	4,222	GE3	23.78	263	92.4	575	14.6	1
20	3600	256TC	TEFC	CEM4106T-5	5,515	GE3	23.80	280	91	575	18	1
	1800	256TC	TEFC	CEM2334T-5	5,564	GE3	23.78	289	93	575	19.2	1
25	1800	284TC	TEFC	CEM4103T-5	7,296	GE3	27.76	401	93.6	575	24	1
30	1800	286TC	TEFC	CEM4104T-5	8,418	GE3	27.76	449	93.6	575	31	1

(a) See notes on inside back flap.

■ Cast iron frame

Custom induction motors available up to 30,000 Hp.

Contact your sales representative for additional information.

*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)