

Three phase, totally enclosed, C-Face, foot mounted

1/3 thru 20 Hp

IP55



Features:

- 300 series stainless steel hardware
- Neoprene gaskets
- Double sealed ball bearings
- Lip and V-Ring seal on DE
- White epoxy, corrosion resistant finish
- Stainless steel shaft extension
- 3 year warranty

Applications:

- Food processing
- Wet environment
- Conveyors
- Packaging
- Pumps and wastewater

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1/3	1800	56C	TENV	CWDM3534	891	WDW	11.06	33	75.5	208-230/460	0.7	1	
		56C	TENV	CWDM3537	995	WDW	11.06	29	70	208-230/460	0.9	1, 12	
	3600	56HC	TENV	CWDM3537-H	995	WDW	11.91	37	70	208-230/460	0.9	1, 12	
1/2	1800	56C	TENV	CWDM3538	1,077	WDW	11.06	28	80	230/460	0.8	1, 12, 30	
		56HC	TENV	CWDM3538-H	1,077	WDW	11.91	33	80	230/460	0.8	1, 12	
	1200	56C	TENV	CWDM3539	1,360	WDW	12.06	37	78.5	208-230/460	1	1, 12	
3/4	1200	56HC	TENV	CWDM3539-H	1,360	WDW	11.91	37	78.5	208-230/460	1	1, 12	
		56C	TENV	CWDM3541	1,042	WDW	11.07	35	80	230/460	1.1	1, 12, 30	
		56HC	TENV	CWDM3541-H	1,042	WDW	11.91	34	80	230/460	1.1	1, 12	
	1800	56C	TENV	CWDM3542	1,167	WDW	11.07	29	78.5	230/460	1.4	1, 12, 30	
		56HC	TENV	CWDM3542-H	1,167	WDW	11.91	30	78.5	230/460	1.4	1, 12, 30	
		56C	TENV	CWDM3543	1,642	WDW	12.94	46	80	208-230/460	1.4	1	
	3600	56HC	TENV	CWDM3543-H	1,642	WDW	12.78	45	81.5	208-230/460	1.4		
		56C	TEFC	CEWDM3545	1,711	WDW	12.24	33	77	230/460	1.4	1, 12	
		56C	TENV	CEWDM3545	1,615	WDW	11.06	35	82.5	230/460	1.3		
		56HC	TENV	CEWDM3545-H	1,615	WDW	11.91	35	82.5	230/460	1.3	1, 12, 30	
		143TC	TENV	CEWDM3545T	1,675	WDW	12.12	35	82.5	230/460	1.3	1	
		56C	TENV	CEWDM3546	1,719	WDW	12.06	41	85.5	230/460	1.5	30	
1	1800	56HC	TENV	CEWDM3546-H	1,719	WDW	11.91	39	85.5	230/460	1.5	1, 30	
		143TC	TENV	CEWDM3546T	1,754	WDW	12.13	37	85.5	230/460	1.5	30	
		56C	TEFC	CEWDM3556	1,930	WDW	13.24	43	82.5	230/460	1.8	1, 30	
	1200	56HC	TEFC	CEWDM3556-H	1,930	WDW	13.08	41	82.5	230/460	1.8	1	
		145TC	TEFC	CEWDM3556T	1,981	WDW	13.28	41	82.5	230/460	1.8	1	
		900	182TC	TEFC	CEWDM3617T	3,089	WDW	16.54	65	75.5	230/460	2.3	1, 30
3600	56C	TENV	CEWDM3550	1,759	WDW	12.07	46	85.5	230/460	2	1, 30		
	56HC	TENV	CEWDM3550-H	1,759	WDW	11.91	48	85.5	230/460	2	1		
	143TC	TENV	CEWDM3550T	1,797	WDW	12.12	48	85.5	230/460	2	1		
	56C	TENV	CEWDM3554	1,798	WDW	12.94	50	86.5	230/460	2.1	30		
	1800	56HC	TENV	CEWDM3554-H	1,798	WDW	12.78	56	86.5	230/460	2.1		
		145TC	TENV	CEWDM3554T	1,836	WDW	13.00	48	86.5	230/460	2.1	30	
1 1/2	1200	182TC	TEFC	CEWDM3607T	2,139	WDW	16.54	72	87.5	230/460	2.4	1, 30	
		900	184TC	TEFC	CEWDM3618T	3,595	WDW	18.04	101	78.5	230/460	3	1
		56HCY	TEFC	CEWDM3555	1,902	WDW	13.24	35	85.5	230/460	2.5	1, 30	
	3600	56HC	TEFC	CEWDM3555-H	1,902	WDW	13.08	41	85.5	230/460	2.5	1	
		145TC	TEFC	CEWDM3555T	1,940	WDW	13.28	45	85.5	230/460	2.5	1, 30	
		56C	TEFC	CEWDM3558	1,961	WDW	14.12	48	86.5	230/460	2.9	1, 30	
2	1800	56HC	TEFC	CEWDM3558-H	1,961	WDW	13.96	48	86.5	230/460	2.9	1, 30	
		145TC	TEFC	CEWDM3558T	2,024	WDW	13.28	46	86.5	230/460	2.9	1, 30	
		145TC	TENV	CEWDM3558T	1,976	WDW	14.37	54	88.5	230/460	2.7	1, 30	
	1200	184TC	TEFC	CEWDM3614T	2,373	WDW	18.04	93	88.5	230/460	3.5	1, 30	
		900	213TC	TEFC	CEWDM3702T	5,054	WDW	19.78	111	85.5	230/460	3.5	1

(a) See notes on inside back flap.
 Red catalog number indicates **NEW** product.

Information

General purpose
Single phase

General purpose
Three phase

Severe duty

Large Motors
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty