

Condenser fan, three phase, ODP, “belly band” round body

1/2 thru 1 1/2 Hp

IP22



Features:

- 6" long shaft with flat and keyway
- Terminal panel for ease of connectivity
- Automatic thermal overload protection
- Lubed for life double shielded bearings

Applications:

- Fans
- Pumps
- Blowers
- Condensers
- Air handling
- HVAC systems
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/2	1200	48YZ	CFM3036A	932	HV3	14.29	25	72	208-230/460	1.2	2, 20
		56YZ	CFM3136A	965	HV3	15.30	28	70	208-230/460	1.2	
3/4	1200	48YZ	CFM3046A	1,011	HV3	16.02	33	77	208-230/460	1.5	2, 20
		56YZ	CFM3146A	1,042	HV3	15.55	33	75.5	208-230/460	1.4	
1	1200	56YZ	CFM3156A	1,189	HV3	16.55	38	75.5	208-230/460	1.8	
1 1/2	1200	56YZ	CFM3166A	1,293	HV3	17.43	48	76	208-230/460	2.5	

(a) See notes on inside back flap.

Condenser fan, three phase, TEAO, “belly band” round body

1/2 Hp

IP44*



Features:

- Low temp grease for use in industrial freezers
- Terminal panel for ease of connectivity
- Automatic thermal overload protection
- Lubed for life double shielded bearings
- 60 and 50 Hz data included for connection at either frequency

Applications:

- Industrial freezers/refrigeration
- Food processing plants
- Low temperature condensers

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/2	1200	56	M3539-TP	1,029	HV3	11.68	29	70	208-230/460	1.2	

(a) See notes on inside back flap.

*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)