

Pump motor

Washdown, jet pump, three phase, TEFC, C-Face 3/4 thru 3 Hp

IP55



Features:

- 300 series stainless steel hardware and shaft extension
- Footless
- Neoprene gaskets
- Double sealed ball bearings
- Lip and V-Ring seal on DE
- White epoxy, corrosion resistant finish
- Easy removable drain plugs

Applications:

- Wet environment
- Pumps and wastewater

Hp	RPM	NEMA Frame	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Footless									
3/4	3600	56J	JWDM3463	12.72	33	68	208-230/460	1.4	1, 30
1	3600	56J	JEWDM3545	12.72	38	78.5	208-230/460	1.6	1, 30
1 1/2	3600	56J	JEWDM3550	13.72	41	84	208-230/460	2	1, 30
2	3600	56J	JEWDM3555	13.72	41	85.5	230/460	2.5	1, 30
3	3600	56J	JEWDM3559	15.97	64	87.5	208-230/460	3.5	1, 30
Foot mounted									
3/4	3600	56J	CJWDM3463	12.72	33	68	208-230/460	1.4	1, 30
1	3600	56J	CJEWDM3545	12.72	38	78.5	208-230/460	1.6	1, 30
1 1/2	3600	56J	CJEWDM3550	13.72	41	84	208-230/460	2	1, 30
2	3600	56J	CJEWDM3555	13.72	41	85.5	230/460	2.5	1, 30
3	3600	56J	CJEWDM3559	15.98	64	87.5	208-230/460	3.5	1, 30

(a) See notes on inside back flap.