

Information

**Jet pump, single phase, ODP**

1/3 thru 3 Hp

**IP23****Features:**

- Automatic thermal overload protection
- Corrosion resistant stainless steel shaft extension
- Slotted opposite DE shaft for easy installation
- Superior switch design provides optimized torque profiles
- Optimized airflow design providing higher horsepower in a smaller package

**Applications:**

- Industrial pumps
- Swimming pool pumps
- General purpose pumps
- Commercial machinery
- Food and beverage
- Wastewater
- Agricultural

General purpose  
Single phaseGeneral purpose  
Three phase

Severe duty

Large Motors  
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>Foot mounted</b>											
1/3	3600	56J	<b>CJL1205A</b>	547	PJ1	11.91	23	58	115/230	3.1	
	1800	56J	<b>CJL1301A</b>	818	PJ1	11.89	23	60	115/208-230	3	30
1/2	3600	56J	<b>CJL1303A</b>	566	PJ1	12.51	30	66	115/230	3.7	
	1800	56J	<b>CJL1304A</b>	925	PJ1	12.14	25	62	115/230	4.2	30
3/4	3600	56J	<b>CJL1306A</b>	723	PJ1	13.39	30	69	115/230	5.5	
	1800	56J	<b>CJL1307A</b>	1,060	PJ1	12.25	35	63	115/230	5.4	
1	3600	56J	<b>CJL1309A</b>	741	PJ1	13.89	32	65	115/208-230	7	30
1 1/2	3600	56J	<b>CJL1313A</b>	1,028	PJ1	13.89	37	78.5	115/230	6.5	
2	3600	56J	<b>CJL1317A</b>	1,375	PJ1	13.25	45	70	115/230	13	30
<b>Footless</b>											
1/3	3600	56J	<b>JL1205A</b>	479	PJ1	11.89	25	58	115/230	3.1	
	1800	56J	<b>JL1301A</b>	552	PJ1	11.89	23	60	115/230	3	30
1/2	3600	56J	<b>JL1303A</b>	538	PJ1	12.51	26	66	115/230	3.7	
	1800	56J	<b>JL1304A</b>	649	PJ1	12.14	25	62	115/230	4.2	30
3/4	3600	56J	<b>JL1306A</b>	708	PJ1	13.39	33	69	115/230	5.5	
	1800	56J	<b>JL1307A</b>	818	PJ1	13.89	33	68	115/230	5.1	30
1	3600	56J	<b>JL1309A</b>	734	PJ1	13.89	32	65	115/230	7	30
1 1/2	3600	56J	<b>JL1313A</b>	1,024	PJ1	13.89	36	78.5	115/230	6.5	
2	3600	56J	<b>JL1317A</b>	1,263	PJ1	13.25	45	70	115/230	13	30
3	3600	56J	<b>JL1323A</b>	1,296	PJ1	14.13	52	82.5	230	13	30

(a) See notes on inside back flap.

All threaded shaft, single phase motors are connected single rotation - CCW when viewing drive end.

**All above ratings can be UL 1081 compliant through MOD Express®.****See M30A in the MOD Express program section of this catalog for more details.**