

Information

Jet pump, three phase, ODP

1/3 thru 3 Hp

IP23General purpose
Single phaseGeneral purpose
Three phase**Features:**

- Corrosion resistant stainless steel shaft extension
- Slotted opposite DE shaft for easy installation
- Dynamically balanced rotor to reduce noise and increase bearing life
- Optimized airflow design providing higher horsepower in a smaller package

Applications:

- Industrial pumps
- Swimming pool pumps
- General purpose pumps
- Commercial machinery
- Food and beverage
- Wastewater
- Agricultural

Severe duty

Large Motors
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Footless											
1/3	3600	56J	JM3006	527	PJ3	11.72	19	62	230/460	0.8	30
	1800	56J	JM3107	557	PJ3	11.72	21	70	230/460	1.2	30
1/2	3600	56J	JM3108	665	PJ3	11.85	23	74	230/460	1	30
	1800	56J	JM3111	660	PJ3	11.72	23	74	208-230/460	1.5	
3/4	3600	56J	JM3112	734	PJ3	12.34	27	75.5	208-230/460	1.5	
	1800	56J	JM3115	734	PJ3	12.34	32	77	230/460	1.6	30
1	3600	56J	JM3116	805	PJ3	13.22	30	78.5	208-230/460	1.7	1
	1800	56J	JM3120	876	PJ3	13.22	30	74	230/460	2.2	30
1 1/2	3600	56J	JM3154	958	PJ3	13.72	34	77	208-230/460	2.8	
	1800	56J	JM3155	1,041	PJ3	13.72	35	82.5	230/460	2.7	30
2	3600	56J	JM3158	1,235	PJ3	13.72	42	80	208-230/460	4	
	1800	56J	JM3158	1,235	PJ3	13.72	42	80	208-230/460	4	
Foot mounted											
1/3	3600	56J	CJM3104	631	PJ3	11.85	22	68	230/460	0.8	30
	1800	56J	CJM3107	578	PJ3	11.72	22	70	230/460	1.2	30
1/2	3600	56J	CJM3108	705	PJ3	11.72	24	74	230/460	1	30
	1800	56J	CJM3111	660	PJ3	11.72	28	74	208-230/460	1.5	
3/4	3600	56J	CJM3112	756	PJ3	12.34	27	75.5	208-230/460	1.5	
	1800	56J	CJM3115	738	PJ3	12.34	29	77	230/460	1.6	30
1	3600	56J	CJM3120	899	PJ3	13.22	31	81.5	230/460	2	30
	1800	56J	CJM3155	1,069	PJ3	13.72	34	82.5	230/460	2.7	30
1 1/2	3600	56J	CJM3158	1,265	PJ3	13.74	41	80	208-230/460	4	
	1800	56J	CJM3158	1,265	PJ3	13.74	41	80	208-230/460	4	

(a) See notes on inside back flap.

All above ratings can be UL 1081 compliant through MOD Express®.**See M30A in the MOD Express program section of this catalog for more details.**