

Stainless steel, three phase, totally enclosed, C-Face, foot mounted

1/3 thru 20 Hp

IP56



Features:

- 300 series stainless steel motor frame, endplates, conduit box, shaft, base, and hardware
- Four condensate drains in each endplate
- Endplate rabbets sealed
- Labyrinth seals on DE and ODE
- 3 year warranty

Applications:

- Food processing
- Packaging
- Pumps and wastewater
- Wet environment

| Hp | RPM | NEMA Frame | Enclosure | Catalog Number | List Price | Disc. Sym. | "C" Dim. | Aprx. Wt. (lb) | Full Load Efficiency | Voltage | Full Load Amps | Notes (a) |
|---------------------|-------|------------|---------------------|----------------------|----------------------|------------|----------|----------------|----------------------|-------------|----------------|-----------|
| 230/460 volt | | | | | | | | | | | | |
| 1/3 | 3600 | 56C | TENV | CSSWDM3457 | 1,736 | WDS | 11.09 | 33 | 74 | 208-230/460 | 0.6 | 1, 30 |
| | 1800 | 56C | TENV | CSSWDM3534 | 1,826 | WDS | 11.09 | 33 | 75.5 | 208-230/460 | 0.7 | 1, 12, 30 |
| 1/2 | 3600 | 56C | TENV | CSSWDM3537 | 2,050 | WDS | 11.09 | 36 | 70 | 208-230/460 | 0.9 | 1, 30 |
| | | 56HC | TENV | CSSWDM3537-H | 2,050 | WDS | 11.97 | 37 | 70 | 208-230/460 | 0.9 | 1 |
| | 1800 | 56C | TENV | CSSWDM3538 | 2,200 | WDS | 11.09 | 37 | 80 | 208-230/460 | 0.9 | 1, 12, 30 |
| | | 56HC | TENV | CSSWDM3538-H | 2,200 | WDS | 11.97 | 33 | 80 | 208-230/460 | 0.9 | 1 |
| 3/4 | 1200 | 56HC | TENV | CSSWDM3539-H | 2,373 | WDS | 11.97 | 37 | 77 | 208-230/460 | 0.9 | 1 |
| | | 56C | TENV | CSSWDM3541 | 2,119 | WDS | 11.09 | 43 | 80 | 230/460 | 1.1 | 1, 12, 30 |
| | 3600 | 56HC | TENV | CSSWDM3541-H | 2,119 | WDS | 11.97 | 34 | 80 | 230/460 | 1.1 | 1,12 |
| | | 56C | TENV | CSSWDM3542 | 2,277 | WDS | 11.09 | 42 | 82.5 | 208-230/460 | 1.1 | 1, 12, 30 |
| | 1800 | 56HC | TENV | CSSWDM3542-H | 2,277 | WDS | 11.97 | 34 | 82.5 | 208-230/460 | 1.1 | 1,12 |
| | | 1200 | 56HC | TENV | CSSWDM3543-H | 2,575 | WDS | 11.97 | 51 | 82.5 | 230/460 | 1.3 |
| 1 | 3600 | 56C | TENV | CESSWDM3545 | 2,323 | WDS | 11.09 | 39 | 82.5 | 230/460 | 1.4 | 12 |
| | | 56HC | TENV | CESSWDM3545-H | 2,323 | WDS | 11.97 | 38 | 82.5 | 230/460 | 1.4 | 12 |
| | 1800 | 56C | TENV | CESSWDM3546 | 2,314 | WDS | 11.09 | 41 | 85.5 | 230/460 | 1.5 | 1, 30 |
| | | 56HC | TENV | CESSWDM3546-H | 2,314 | WDS | 11.97 | 41 | 85.5 | 230/460 | 1.5 | |
| | 1200 | 56HC | TENV | CESSWDM3546T | 2,348 | WDS | 13.42 | 52 | 87.5 | 230/460 | 1.5 | 1, 30 |
| | 1 1/2 | 3600 | 56C | TENV | CESSWDM3550 | 2,337 | WDS | 12.97 | 56 | 85.5 | 230/460 | 1.8 |
| 56HC | | | TENV | CESSWDM3550-H | 2,337 | WDS | 12.85 | 50 | 85.5 | 230/460 | 1.8 | 1,30 |
| 1437C | | TENV | CESSWDM3550T | 2,356 | WDS | 13.23 | 60 | 85.5 | 230/460 | 1.8 | 1, 30 | |
| | | 56C | TEFC | CESSWDM3554 | 2,358 | WDS | 13.34 | 41 | 86.5 | 230/460 | 2.2 | 1, 30 |
| 1800 | | 56HC | TEFC | CESSWDM3554-H | 2,358 | WDS | 13.03 | 45 | 86.5 | 230/460 | 2.2 | 1,30 |
| | | 1457C | TEFC | CESSWDM3554T | 2,393 | WDS | 13.42 | 55 | 87.5 | 230/460 | 2.1 | 1, 30 |
| 2 | 3600 | 56HC | TENV | CESSWDM3555-H | 3,114 | WDS | 12.85 | 61 | 88.5 | 230/460 | 2.4 | |
| | | 1457C | TEFC | CESSWDM3555T | 2,855 | WDS | 14.30 | 60 | 86.5 | 208-230/460 | 2.5 | 1, 30 |
| | 1800 | 56C | TEFC | CESSWDM3558 | 2,841 | WDS | 13.34 | 45 | 86.5 | 230/460 | 2.8 | 8, 30 |
| | | 56HC | TEFC | CESSWDM3558-H | 2,841 | WDS | 13.03 | 45 | 86.5 | 230/460 | 2.8 | |
| | 1457C | TEFC | CESSWDM3558T | 2,875 | WDS | 13.42 | 45 | 86.5 | 230/460 | 2.8 | 8, 30 | |
| | | 3600 | 1457C | TEFC | CESSWDM3559T | 3,440 | WDS | 15.67 | 74 | 86.5 | 208-230/460 | 3.7 |
| 3 | 1800 | 1827C | TEFC | CESSWDM3610T | 3,674 | WDS | 16.82 | 90 | 88.5 | 230/460 | 3.7 | 1, 30 |
| | | 1827C | TEFC | CESSWDM3611T | 3,361 | WDS | 18.32 | 94 | 89.5 | 230/460 | 4.2 | 1, 30 |
| | 3600 | 1847C | TEFC | CESSWDM3613T | 3,909 | WDS | 18.32 | 106 | 90.2 | 230/460 | 5.7 | 30 |
| 5 | 1800 | 1847C | TEFC | CESSWDM3615T | 3,782 | WDS | 18.32 | 112 | 89.5 | 230/460 | 6.5 | |
| | | 3600 | 2137C | TEFC | CESSWDM3709T | 4,588 | WDS | 19.03 | 166 | 91 | 230/460 | 8.3 |
| | 1800 | 2137C | TEFC | CESSWDM3710T | 4,731 | WDS | 20.16 | 137 | 91.7 | 230/460 | 9.5 | 1 |
| 10 | 3600 | 2157C | TEFC | CESSWDM3711T | 5,119 | WDS | 20.16 | 184 | 91.7 | 230/460 | 10.6 | 1, 30 |
| | | 1800 | 2157C | TEFC | CESSWDM3714T | 5,218 | WDS | 21.66 | 190 | 92.4 | 230/460 | 12.5 |
| | 3600 | 2157C | TEFC | CESSWDM3713T | 7,682 | WDS | 21.66 | 187 | 91.7 | 230/460 | 17 | 8,30 |
| 15 | 1800 | 2547C | TEFC | CESSWDM23994T | 10,448 | WDS | 24.67 | 293 | 91 | 230/460 | 16.5 | 1, 30 |
| | | 2547C | TEFC | CESSWDM23933T | 10,283 | WDS | 24.67 | 293 | 92.4 | 230/460 | 17.5 | 1, 30 |
| 20 | 3600 | 2567C | TEFC | CESSWDM41906T | 11,993 | WDS | 24.67 | 312 | 91 | 230/460 | 21.5 | 2 |
| | | 1800 | 2567C | TEFC | CESSWDM23934T | 11,925 | WDS | 24.67 | 299 | 93 | 230/460 | 24 |

(a) See notes on inside back flap
Red catalog number indicates **NEW** product.

Information
 General purpose Single phase
 General purpose Three phase
 Severe duty
 Large Motors and Generators
 Washdown duty
 Explosion proof
 Pump
 HVAC
 Farm duty