

841XL, three phase, totally enclosed, 460 volts and 575 volts

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
575 volts (continued)											
15	3600	254T	ECP82394T-5	5,130	SD8	24.78	305	91.7	575	13.7	1
	1800	254T	ECP82333T-5	4,739	SD8	24.78	318	92.4	575	14.1	1
	1200	284T	ECP84100T-5	7,406	SD8	27.93	445	91.7	575	15.6	1
20	3600	256T	ECP84106T-5	5,882	SD8	24.78	324	91.7	575	17.9	1
	1800	256T	ECP82334T-5	5,124	SD8	24.78	361	93	575	18.3	1
	1200	286T	ECP84102T-5	9,981	SD8	27.93	443	91.7	575	21	1
25	3600	284TS	ECP84107T-5	7,191	SD8	26.56	429	91.7	575	23	1
	1800	284T	ECP84103T-5	6,646	SD8	27.93	345	93.6	575	24	1
	1200	324T	ECP84111T-5	10,519	SD8	30.66	623	93	575	25.4	1
30	3600	286TS	ECP84108T-5	8,614	SD8	26.56	422	91.7	575	27	1
	1800	286T	ECP84104T-5	7,826	SD8	27.93	489	93.6	575	28	1
	1200	326T	ECP84117T-5	13,689	SD8	30.66	635	93	575	31	1
40	3600	324TS	ECP84109T-5	11,785	SD8	29.16	624	92.4	575	35	1
	1800	324T	ECP84110T-5	10,420	SD8	30.66	635	94.1	575	37	1
	1200	364T	ECP84308T-5	16,771	SD8	33.49	922	94.1	575	39.5	1
50	3600	326TS	ECP84114T-5	12,293	SD8	29.16	662	93	575	44	1
	1800	326T	ECP84115T-5	12,233	SD8	30.66	653	94.5	575	45	1
	1200	365T	ECP84312T-5	19,527	SD8	33.49	924	94.1	575	49.3	1
60	3600	364TS	ECP84310T-5	17,743	SD8	31.37	932	95	575	52	1
	1800	364T	ECP84314T-5	17,565	SD8	33.49	937	95	575	54.4	1
	1200	404T	ECP84403T-5	23,134	SD8	38.04	1275	95	575	55.2	1
75	3600	365TS	ECP84313T-5	20,061	SD8	31.37	998	94.5	575	64.5	1
	1800	365T	ECP84316T-5	19,939	SD8	33.49	985	95.4	575	68.7	1
	1200	405T	ECP84404T-5	28,021	SD8	38.04	1283	94.5	575	69.5	1
100	3600	405TS	ECP84402T-5	24,113	SD8	35.04	1287	95	575	88	1
	1800	405T	ECP84400T-5	25,217	SD8	38.04	1304	95.4	575	89.6	1
	1200	444T	ECP84409T-5	30,822	SD8	44.75	1885	95	575	92	1
125	3600	444TS	ECP84412T-5	28,200	SD8	40.98	1799	95.4	575	109	1
	1800	444T	ECP84410T-5	28,604	SD8	44.75	1915	95.8	575	111	1
	1200	445T	ECP84411T-5	34,984	SD8	44.75	2000	95.4	575	114	1
150	3600	445TS	ECP84413T-5	32,406	SD8	40.98	2062	96.2	575	131	1
	1800	445T	ECP84406T-5	33,827	SD8	44.75	1886	96.2	575	132	1
	1200	447T	ECP844156TR-5	40,811	SD8	48.24	2595	95.8	575	136	1, 5
200	3600	447TS	ECP84416T-5	42,841	SD8	44.48	2182	96.2	575	177	1
	1800	447T	ECP84407T-5	40,698	SD8	48.24	2606	96.2	575	178	1
	1200	447T	ECP84407TR-5	42,626	SD8	48.24	2618	96.2	575	178	1, 5
250	3600	449T	ECP844206TR-5	53,586	SD8	53.24	3100	95.8	575	180	1, 5
	1800	449T	ECP844252T-5	69,026	SD8	49.48	2784	96.2	575	212	1
	1200	449T	ECP84408T-5	51,952	SD8	53.24	2932	96.2	575	220	1
300	3600	449T	ECP84408TR-5	53,828	SD8	53.24	2732	96.2	575	220	1, 5
	1800	449T	ECP844256TR-5	76,579	SD8	53.47	3125	95.8	575	229	1, 5
	1200	L449T	ECP844306TR-5	87,297	SD8	60.47	3683	95.8	575	272	1, 5

(a) See notes on inside back flap

■ Cast iron frame