

General purpose, F-2 mount, three phase, TEFC and ODP, foot mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Open drip proof, 230/460 volts (continued)											
20	1800	256T	EFM2515T	4,276	G03	21.69	226	93	230/460	23.5	1, 30
25	1800	284T	EFM2531T	5,213	G03	25.06	313	93.6	230/460	30	1, 30
30	1800	286T	EFM2535T	5,701	G03	25.06	339	94.1	230/460	35	1, 30
40	1800	324T	EFM2539T	7,436	G03	27.19	392	94.1	230/460	49	1, 30
50	1800	326T	EFM2543T	8,205	G03	27.69	547	94.5	230/460	57	1, 30
60	1800	364T	EFM2547T	10,331	G03	30.69	622	95	230/460	68	1, 30
Open drip proof, 200 volts											
2	1800	145T	EFM3157T-8	1,324	G03	12.12	40	86.5	200	6.5	1, 68
3	1800	182T	EFM3211T-8	1,433	G03	15.00	70	89.5	200	9.7	1, 68
5	1800	184T	EFM3218T-8	1,574	G03	16.50	82	89.5	200	15.3	1, 68
7 1/2	1800	213T	EFM3311T-8	2,307	G03	16.32	111	91	200	22.3	1, 68
10	1800	215T	EFM3313T-8	2,793	G03	17.45	127	91.7	200	29.5	1, 68
15	1800	254T	EFM2513T-8	3,942	G03	21.69	209	93	200	40.7	1, 68
20	1800	256T	EFM2515T-8	4,326	G03	21.69	226	93	200	54.3	1, 24, 69

(a) See notes on inside back flap.

Custom induction motors available up to 30,000 Hp.

Contact your sales representative for additional information.