

## Super-E®, three phase, ODP, foot mounted

1 thru 100 Hp

IP22



### Features:

- External provisions for bearing current mitigation
- Designed for longevity with 3 year warranty
- Suitable for inverter use per NEMA MG1 Part 31.4.4.2

### Applications:

- Fans
- Pumps
- Blowers
- Air handling
- HVAC systems
- Variable speed applications
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>230/460 volt</b>											
1	1800	143T	<b>EHM3116T</b>	952	HV3	11.12	35	85.5	230/460	1.5	30
1 1/2	1800	145T	<b>EHM3154T</b>	988	HV3	11.62	37	86.5	230/460	2.2	30
2	1800	145T	<b>EHM3157T</b>	1,062	HV3	12.13	41	86.5	230/460	2.9	30
3	1800	182T	<b>EHM3211T</b>	1,139	HV3	15.00	72	89.5	230/460	4.2	30
	1200	213T	<b>EHM3305T</b>	1,879	HV3	16.32	114	88.5	230/460	4.5	30
5	1800	184T	<b>EHM3218T</b>	1,237	HV3	16.50	85	89.5	230/460	6.6	30
	1200	215T	<b>EHM3309T</b>	2,445	HV3	17.45	141	89.5	230/460	7.4	30
7 1/2	1800	213T	<b>EHM3311T</b>	1,798	HV3	16.32	115	91	230/460	9.7	30
	1200	254T	<b>EHM2506T</b>	2,920	HV3	23.19	248	90.2	230/460	11	30
10	1800	215T	<b>EHM3313T</b>	2,164	HV3	17.45	127	91.7	230/460	12.5	30
	1200	256T	<b>EHM2511T</b>	3,782	HV3	23.19	260	91.7	230/460	14.3	30
15	1800	254T	<b>EHM2523T</b>	3,051	HV3	21.69	212	93	230/460	17.7	30
	1200	284T	<b>EHM2524T</b>	5,080	HV3	23.81	285	91.7	230/460	20.5	30
20	1800	256T	<b>EHM2515T</b>	3,817	HV3	21.69	225	93	230/460	23.5	30
	1200	286T	<b>EHM2528T</b>	6,170	HV3	23.81	375	92.4	230/460	27	30
25	1800	284T	<b>EHM2531T</b>	4,644	HV3	25.06	345	93.6	230/460	30	30
	1200	324T	<b>EHM2532T</b>	7,441	HV3	27.69	393	93	230/460	34	30
30	1800	286T	<b>EHM2535T</b>	6,605	HV3	25.06	339	94.1	230/460	35	30
	1200	326T	<b>EHM2536T</b>	7,759	HV3	28.69	482	93.6	230/460	38	30
40	1800	324T	<b>EHM2539T</b>	7,441	HV3	27.19	433	94.1	230/460	49	30
50	1800	326T	<b>EHM2543T</b>	8,102	HV3	27.69	469	94.5	230/460	57	30
60	1800	364T	<b>EHM2547T</b>	9,160	HV3	29.94	582	95	230/460	68	30
75	1800	365T	<b>EHM2551T</b>	11,234	HV3	33.72	752	95	230/460	87	30
100	1800	404T	<b>EHM2555T</b>	12,804	HV3	36.97	911	95.4	230/460	113	30
<b>230/460 volt, F2 mounting</b>											
2	1800	145T	<b>EHF3157T</b>	1,062	HV3	12.13	49	86.5	230/460	2.9	30
3	1800	182T	<b>EHF3211T</b>	1,139	HV3	15.00	68	89.5	230/460	4.2	30
5	1800	184T	<b>EHF3218T</b>	1,798	HV3	16.50	82	89.5	230/460	6.6	30
7 1/2	1800	213T	<b>EHF3311T</b>	2,164	HV3	16.32	115	91	230/460	9.7	30
10	1800	215T	<b>EHF3313T</b>	2,437	HV3	17.45	127	91.7	230/460	12.5	30
15	1800	254T	<b>EHF2523T</b>	3,051	HV3	21.69	212	93	230/460	17.7	30
20	1800	256T	<b>EHF2515T</b>	3,817	HV3	21.69	227	93	230/460	23.5	30
25	1800	284T	<b>EHF2531T</b>	4,644	HV3	25.06	301	93.6	230/460	30	30
30	1800	286T	<b>EHF2535T</b>	5,075	HV3	25.06	328	94.1	230/460	35	30
40	1800	324T	<b>EHF2539T</b>	6,605	HV3	27.19	429	94.1	230/460	49	30
50	1800	326T	<b>EHF2543T</b>	8,102	HV3	27.69	466	94.5	230/460	57	30

(a) See notes on inside back flap.