

General purpose HVAC

three phase, ODP, foot mounted 1 thru 100 Hp

IP22



Features:

- External provisions for bearing current mitigation
- Designed for longevity with 3 year warranty
- Suitable for inverter use per NEMA MG1 Part 31.4.4.2

Applications:

- Fans
- Pumps
- Blowers
- Air handling
- HVAC systems
- Variable speed applications
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
230/460 volt									
1	1800	143T	EHM3116T	11.12	35	85.5	230/460	1.5	30
1 1/2	1800	145T	EHM3154T	11.62	37	86.5	230/460	2.2	30
2	1800	145T	EHM3157T	12.13	41	86.5	230/460	2.9	30
3	1800	182T	EHM3211T	15.00	72	89.5	230/460	4.2	30
	1200	213T	EHM3305T	16.32	114	88.5	230/460	4.5	30
5	1800	184T	EHM3218T	16.50	85	89.5	230/460	6.6	30
	1200	215T	EHM3309T	17.45	141	89.5	230/460	7.4	30
7 1/2	1800	213T	EHM3311T	16.32	115	91	230/460	9.7	30
	1200	254T	EHM2506T	23.19	248	90.2	230/460	11	30
10	1800	215T	EHM3313T	17.45	127	91.7	230/460	12.5	30
	1200	256T	EHM2511T	23.19	260	91.7	230/460	14.3	30
15	1800	254T	EHM2523T	21.69	212	93	230/460	17.7	30
	1200	284T	EHM2524T	23.81	285	91.7	230/460	20.5	30
20	1800	256T	EHM2515T	21.69	225	93	230/460	23.5	30
	1200	286T	EHM2528T	23.81	375	92.4	230/460	27	30
25	1800	284T	EHM2531T	25.06	345	93.6	230/460	30	30
	1200	324T	EHM2532T	27.69	393	93	230/460	34	30
30	1800	286T	EHM2535T	25.06	339	94.1	230/460	35	30
	1200	326T	EHM2536T	28.69	482	93.6	230/460	38	30
40	1800	324T	EHM2539T	27.19	433	94.1	230/460	49	30
50	1800	326T	EHM2543T	27.69	469	94.5	230/460	57	30
60	1800	364T	EHM2547T	29.94	582	95	230/460	68	30
75	1800	365T	EHM2551T	33.72	752	95	230/460	87	30
100	1800	404T	EHM2555T	36.97	911	95.4	230/460	113	30
230/460 volt, F2 mounting									
2	1800	145T	EHFM3157T	12.13	49	86.5	230/460	2.9	30
3	1800	182T	EHFM3211T	15.00	68	89.5	230/460	4.2	30
5	1800	184T	EHFM3218T	16.50	82	89.5	230/460	6.6	30
7 1/2	1800	213T	EHFM3311T	16.32	115	91	230/460	9.7	30
10	1800	215T	EHFM3313T	17.45	127	91.7	230/460	12.5	30
15	1800	254T	EHFM2523T	21.69	212	93	230/460	17.7	30
20	1800	256T	EHFM2515T	21.69	227	93	230/460	23.5	30
25	1800	284T	EHFM2531T	25.06	301	93.6	230/460	30	30
30	1800	286T	EHFM2535T	25.06	328	94.1	230/460	35	30
40	1800	324T	EHFM2539T	27.19	429	94.1	230/460	49	30
50	1800	326T	EHFM2543T	27.69	466	94.5	230/460	57	30

(a) See notes on inside back flap.