

Super-E, three phase, ODP, foot mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
200 volt											
1	1800	143T	EHM3116T-8	952	HV3	11.12	34	85.5	200	3.5	
1 1/2	1800	145T	EHM3154T-8	988	HV3	11.62	38	86.5	200	5.1	
2	1800	145T	EHM3157T-8	1,062	HV3	12.13	41	86.5	200	6.5	
3	1800	182T	EHM3211T-8	1,139	HV3	15.00	71	89.5	200	9.7	
5	1800	184T	EHM3218T-8	1,237	HV3	16.50	85	89.5	200	15.3	
7 1/2	1800	213T	EHM3311T-8	1,798	HV3	16.32	115	91	200	22.2	
10	1800	215T	EHM3313T-8	2,164	HV3	17.45	120	91.7	200	29.5	30
15	1800	254T	EHF2523T-8	3,043	HV3	21.69	211	93	200	40.7	6, 30
		254T	EHM2523T-8	3,051	HV3	21.69	210	93	200	40.7	30
20	1800	256T	EHM2515T-8	3,817	HV3	21.69	226	93	200	54.3	30
25	1800	284T	EHM2531T-8	4,644	HV3	25.06	369	93.6	200	70	
30	1800	286T	EHM2535T-8	5,075	HV3	25.06	331	94.1	200	81	
40	1800	324T	EHM2539T-8	6,605	HV3	26.69	434	94.1	200	108	
50	1800	326T	EHM2543T-8	8,102	HV3	27.69	459	94.5	200	132	

(a) See notes on inside back flap.

Information

General purpose
Single phase

General purpose
Three phase

Severe duty

Large Motors
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty