

Close-coupled pump, three phase, TEFC

Hp	RPM	NEMA Frame	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
230/460 volts (continued)									
25	3600	284JM	EJMM4107T	26.96	353	91.7	230/460	29	20, 30
		284JP	EJPM4107T	29.84	349	91.7	230/460	29	20, 30
	1800	284JM	EJMM4103T	28.64	387	93.6	230/460	30	1, 30
		284JP	EJPM4103T	31.51	412	93.6	230/460	30	1, 30
30	3600	286JM	EJMM4108T	28.64	406	91.7	230/460	33	1, 30
		286JP	EJPM4108T	31.51	405	91.7	230/460	35	1, 30
	1800	286JM	EJMM4104T	28.64	422	93.6	230/460	36	1, 30
		286JP	EJPM4104T	31.51	452	93.6	230/460	36	1, 30
40	3600	324JM	EJMM4109T	30.64	487	92.4	230/460	45	1, 30
		324JP	EJPM4109T	33.51	498	92.4	230/460	45	1, 30
	1800	324JM	EJMM4110T	30.65	586	94.1	230/460	48	1, 30
		324JP	EJPM4110T	33.41	602	94.1	230/460	48	1, 30
50	3600	326JM	EJMM4114T	30.65	595	93	230/460	56	1, 30
		326JP	EJPM4114T	33.41	604	93	230/460	56	1, 30
	1800	326JM	EJMM4115T	30.65	624	94.5	230/460	58	1, 30
		326JP	EJPM4115T	33.41	646	94.5	230/460	58	1, 30
575 volts									
1	1800	143JM	EJMM3546T-5	15.43	38	85.5	575	1.2	1
1 1/2	3600	143JM	EJMM3550T-5	15.41	38	84	575	1.5	
		145JM	EJMM3554T-5	15.43	41	86.5	575	1.8	1
2	3600	145JM	EJMM3555T-5	15.41	41	85.5	575	2	
		145JM	EJMM3558T-5	15.43	45	86.5	575	2.3	1
3	3600	145JM	EJMM3559T-5	16.29	50	86.5	575	2.9	1
		182JM	EJMM3610T-5	16.69	63	86.5	575	2.9	
	1800	182JM	EJMM3611T-5	18.06	70	89.5	575	3.3	1
		184JM	EJMM3613T-5	18.06	74	88.5	575	4.7	1
5	3600	184JM	EJMM3615T-5	19.56	93	89.5	575	5.3	1
		184JM	EJMM3616T-5	19.56	96	89.5	575	6.8	1
7 1/2	3600	213JM	EJMM3710T-5	20.88	127	91.7	575	7.6	1, 35
		215JM	EJMM3711T-5	19.76	118	90.2	575	9.5	20
10	3600	215JM	EJMM3714T-5	22.38	165	91.7	575	9.6	1, 35
		254JM	EJMM2394T-5	23.07	225	91	575	13.5	1, 35
15	3600	215JM	EJMM3713T-5	22.38	169	91	575	13.4	1
		254JM	EJMM2333T-5	25.30	268	92.4	575	14.6	1, 35

(a) See notes on inside back flap.

Cast iron frame