

Close-coupled pump, three phase, foot mounted, with internal AEGIS® bearing protection ring

Hp	RPM	NEMA Frame	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Open drip proof									
1	1800	143JM	EJMM3116T-G	13.75	37	85.5	230/460	1.5	30
1 1/2	1800	145JM	EJMM3154T-G	13.75	41	86.5	230/460	2.2	30
2	1800	145JM	EJMM3157T-G	14.25	44	86.5	230/460	2.9	30
3	3600	145JM	EJMM3158T-G	15.13	51	85.5	230/460	3.8	30
	1800	182JM	EJMM3211T-G	16.50	74	89.5	230/460	4.2	30
5	3600	182JM	EJMM3212T-G	15.12	64	86.5	230/460	6	30
	1800	184JM	EJMM3218T-G	18.00	88	89.5	230/460	6.6	30
7 1/2	3600	184JM	EJMM3219T-G	16.50	78	88.5	230/460	8.6	30
	1800	213JM	EJMM3311T-G	18.19	120	91	230/460	9.7	30
10	3600	213JM	EJMM3312T-G	18.19	121	89.5	230/460	12	30
	1800	215JM	EJMM3313T-G	19.31	132	91.7	230/460	12.5	30
15	3600	215JM	EJMM3314T-G	18.19	134	90.2	230/460	17.5	30
	1800	254JM	EJMM2513T-G	23.19	213	93	230/460	17.7	30
20	3600	254JM	EJMM2514T-G	23.19	185	91	230/460	23.5	30
	1800	256JM	EJMM2515T-G	24.69	255	93	230/460	24	30
25	3600	256JM	EJMM2516T-G	23.19	233	91.7	230/460	28	30
	1800	284JM	EJMM2531T-G	25.94	377	93.6	230/460	30	30
30	3600	284JM	EJMM2534T-G	24.69	320	91.7	230/460	35	30
	1800	286JM	EJMM2535T-G	26.94	378	94.1	230/460	36	30
40	3600	286JM	EJMM2538T-G	24.69	330	92.4	230/460	46	30
	1800	324JM	EJMM2539T-G	27.44	378	94.1	230/460	49	30
50	3600	324JM	EJMM2542T-G	27.44	375	93	230/460	56	30
	1800	326JM	EJMM2543T-G	27.94	497	94.5	230/460	57	30

(a) See notes on inside back flap.